

Triple Action Carpet & Upholstery Cleaner

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : Triple Action Carpet & Upholstery Cleaner

Product code : BE110261

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses relevant : Carpet cleaner

Uses advised against : Uses other than those identified relevant

Use descriptor system (REACH) :

PC 35 : Washing and cleaning (including the solvent-based products)

1.3. Details of the supplier of the safety data sheet

Registered company name : GS27

Address : 540, rue Gilles de Gennes - Node Park Touraine - 37310 Tauxigny - France

Telephone : 0033 247 737 777 Fax : 0033 247 373 866

www.gs27.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : ORFILA / INRS.

Other emergency numbers

United Kingdom emergency telephone number : 999

European emergency call : 112

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Extremely flammable (F+, R 12).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02

Signal Word :

DANGER

Hazard statements :

H222 Extremely flammable aerosol.

Triple Action Carpet & Upholstery Cleaner

- H229 Pressurised container: May burst if heated.
- Precautionary statements - General :
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- Precautionary statements - Prevention :
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing spray.
- P271 Use only outdoors or in a well-ventilated area.
- Precautionary statements - Response :
- P301 + P312 IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell.
- Precautionary statements - Storage :
- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 122°F.
- Precautionary statements - Disposal :
- P501 Dispose of empty or unused container to waste disposal or household waste in accordance with national regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	67/548/EEC	Note	%
INDEX: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32	GHS02, GHS04 Dgr Flam. Gas 1, H220	F+ F+;R12	C [1] [7]	2.5 <= x % < 10
BUTANE CAS: 34590-94-8 EC: 252-104-2 REACH: 01-2119450011-60			[1]	2.5 <= x % < 10
(2 - METHOXYMETHYLETHOXY)PROPANOL CAS: 1300-72-7 EC: 215-090-9 REACH: 01-2119513350-56	GHS07 Wng Eye Irrit. 2, H319	Xi Xi;R36		0 <= x % < 2.5
XYLENESULFONATE DE SODIUM INDEX: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21	GHS02, GHS04 Dgr Flam. Gas 1, H220	F+ F+;R12	[1] [7]	0 <= x % < 2.5
PROPANE				

Triple Action Carpet & Upholstery Cleaner

CAS: 7632-00-0 EC: 231-555-9 REACH: 01-2119471836-27 SODIUM NITRITE	GHS06, GHS09, GHS03 Dgr Ox. Liq. 3, H272 Acute Tox. 3, H301 Eye Irrit. 2, H319 Aquatic Acute 1, H400 M Acute = 1	T,N,O T;R25 N;R50 O;R8		0 <= x % < 2.5
--	--	---------------------------------	--	----------------

Information on ingredients :

- [7] Propellant gas
- [1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Move victim to fresh air. If symptoms persist, consult a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
If discomfort persists, contact an ophthalmologist immediately.

In the event of splashes or contact with skin :

Rinse with soapy water.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
Keep the person exposed at rest. Do not force vomiting.
Seek medical attention, showing the label.
If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor :

Treat symptomatically. Treatment of overexposure should be based on control of symptoms and the clinical condition of the patient.
The severity of injury, the prognosis of intoxication depend directly on the concentration and duration of exposure.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
Do not breathe in smoke.

Triple Action Carpet & Upholstery Cleaner

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

Information on the flammability properties, see Section 9.

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Firefighters should use standard protective equipment and confined spaces, breathing apparatus (SCBA).

Cool containers / tanks with water spray.

Fold gas / fumes / mists with water spray.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Be careful to the accumulation of flammable vapors

Spills or accidental release, notify relevant authorities in accordance with current regulations.

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Eliminate any possible source of ignition and ventilate the premises.

Avoid spills or further leakage if possible without risk.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

Isolate area.

Evacuate personnel to safe areas.

Ventilate area.

SCBA in confined / if insufficient oxygen / in case of significant emissions.

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

See control measures against fire in Section 5.

See protective measures listed in sections 7 and 8.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Triple Action Carpet & Upholstery Cleaner

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
34590-94-8	308	50	-	-	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm	-	-	-	-
34590-94-8	100 ppm	150 ppm	-	-	-
74-98-6	1000 ppm	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
106-97-8	1000 ml/m3	2400 mg/m3	4(II)	DFG
34590-94-8	50 ml/m3	310 mg/m3	1(I)	DFG, EU
74-98-6	1000 ml/m3	1800 mg/m3	4(II)	DFG

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-
34590-94-8	50	308	-	-	*	84

- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), Mayo 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm	-	-	-	-
34590-94-8	50 ppm	-	-	-	-
74-98-6	1000 ppm	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm	750 ppm	-	-	-

Triple Action Carpet & Upholstery Cleaner

34590-94-8	50 ppm	-	-	-	-
- Netherlands / MAC-waarde (SER, 4 May 2010) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm	-	-	-	-
34590-94-8	50 ppm	-	-	-	-
- Belgium (Order of 19/05/2009, 2010) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	800 ppm	-	-	-	-
34590-94-8	50 ppm	-	-	-	-

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

SODIUM NITRITE (CAS: 7632-00-0)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Inhalation.
Short term systemic effects.
2 mg of substance/m3

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
2 mg of substance/m3

XYLENESULFONATE DE SODIUM (CAS: 1300-72-7)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
7.6 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
53.6 mg of substance/m3

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Ingestion.
Long term systemic effects.
3.8 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
3.8 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
13.2 mg of substance/m3

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
65 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
310 mg of substance/m3

Triple Action Carpet & Upholstery Cleaner

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Ingestion.
Long term systemic effects.
1.67 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
15 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
37.2 mg of substance/m³

Predicted no effect concentration (PNEC):

SODIUM NITRITE (CAS: 7632-00-0)

Environmental compartment:
PNEC :

Soil.
0.000733 mg/kg

Environmental compartment:
PNEC :

Fresh water.
0.0054 mg/l

Environmental compartment:
PNEC :

Sea water.
0.00616 mg/l

Environmental compartment:
PNEC :

Intermittent waste water.
0.0054 mg/l

Environmental compartment:
PNEC :

Fresh water sediment.
0.0195 mg/kg

Environmental compartment:
PNEC :

Marine sediment.
0.0223 mg/kg

Environmental compartment:
PNEC :

Waste water treatment plant.
21 mg/l

XYLENESULFONATE DE SODIUM (CAS: 1300-72-7)

Environmental compartment:
PNEC :

Fresh water.
0.23 mg/l

Environmental compartment:
PNEC :

Intermittent waste water.
2.3 mg/l

Environmental compartment:
PNEC :

Waste water treatment plant.
100 mg/l

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Environmental compartment:
PNEC :

Soil.
2.74 mg/kg

Environmental compartment:
PNEC :

Fresh water.
19 mg/l

Environmental compartment:

Sea water.

Triple Action Carpet & Upholstery Cleaner

PNEC :	1.9 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 190 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 70.2 mg/kg
Environmental compartment: PNEC :	Marine sediment. 7.02 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 4168 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Exposure controls linked to environmental protection

See Section 6, 7, 12 and 13.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Fluid liquid. Spray.
Opacity :	Clear
Color :	Colorless

Important health, safety and environmental information

pH :	11.10 +/- 0.40. Slightly basic.
Boiling point/boiling range :	100 °C.
Explosive properties, lower explosivity limit (%) :	1.5
Explosive properties, upper explosivity limit (%) :	10

Triple Action Carpet & Upholstery Cleaner

Oxidising properties :	Non comburant
Vapour pressure (50°C) :	Above 300 kPa (3 bar).
Density :	1005 g/L à 20°C Method for determining the density : ISO 3507 (Laboratory glassware - Pycnometers).
Water solubility :	Soluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.
Chemical combustion heat :	Not specified.
Inflammation time :	Not specified.
Deflagration density :	Not specified.
Inflammation distance :	Not specified.
Flame height :	Not specified.
Flame duration :	Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- frost
- flames and hot surfaces
- Temperature above 50 ° C. Sparks or source of ignition.

10.5. Incompatible materials

- Acids or bases that can attack the can.
- Excessive moisture can cause external corrosion.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Splashes in the eyes may cause irritation and reversible damage

Triple Action Carpet & Upholstery Cleaner

11.1.1. Substances

Acute toxicity :

SODIUM NITRITE (CAS: 7632-00-0)
Oral route : LD50 = 180 mg/kg
Species : Rat

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)
Oral route : LD50 > 5000 mg/kg
Species : Rat

Dermal route : LD50 = 9510 mg/kg
Species : Rabbit
Other guideline

Other guideline

Skin corrosion/skin irritation :

SODIUM NITRITE (CAS: 7632-00-0)
Irritation : Average score = 0
Effect observed : Overall irritation score
Species : Rabbit
Duration of exposure : 24 h
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)
Corrosivity : No observed effect.

Irritation : No observed effect.
Average score < 1.5
Species : Rabbit
Other guideline

Serious damage to eyes/eye irritation :

SODIUM NITRITE (CAS: 7632-00-0)
Conjunctival redness : 2 <= Average score < 2.5 and effects totally reversible within 21 days of observation
Species : Rabbit
Duration of exposure : 24 h
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

XYLENESULFONATE DE SODIUM (CAS: 1300-72-7)
Conjunctival redness : Average score >= 2.5 and effects totally reversible within 21 days of observation
Duration of exposure : 24 h
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Germ cell mutagenicity :

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)
No mutagenic effect.

Mutagenesis (in vivo) : Negative.

Mutagenesis (in vitro) : Negative.

Triple Action Carpet & Upholstery Cleaner

Carcinogenicity :

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Carcinogenicity Test : Negative.

No carcinogenic effect.

Reproductive toxicant :

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

No toxic effect for reproduction

Specific target organ systemic toxicity - repeated exposure :

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Oral route : C = 1000 mg/kg bodyweight/jour
Duration of exposure : 90 days

Dermal route : C = 4750 mg/kg bodyweight/jour
Duration of exposure : 90 days

Inhalation route : C = 300 ppmV/6h/day
Duration of exposure : 90 days

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

SODIUM NITRITE (CAS: 7632-00-0)

Fish toxicity : LC50 = 0.54 mg/l
Factor M = 1
Species : Oncorhynchus mykiss
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 15.4 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity : ECr50 >= 100 mg/l
Species : Scenedesmus subspicatus
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

Aquatic plant toxicity : Duration of exposure : 72 h

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Fish toxicity : LC50 > 1000 mg/l
Species : Poecilia reticulata
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 1919 mg/l
Species : Daphnia magna

Triple Action Carpet & Upholstery Cleaner

Duration of exposure : 48 h

NOEC > 0.5 mg/l

Species : Daphnia magna

Duration of exposure : 21 days

Algae toxicity :

ECr50 > 969 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 96 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

The surfactants in this product comply with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of Member States and will be provided upon request or at the request of a detergent manufacturer.

12.2.1. Substances

XYLENESULFONATE DE SODIUM (CAS: 1300-72-7)

Biodegradability : Rapidly degradable.

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

(2 - METHOXYMETHYLETHOXY)PROPANOL (CAS: 34590-94-8)

Octanol/water partition coefficient : $\log K_{ow} = 1.01$

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Do not pierce or burn even after use.

Local arrangements :

Recyclable metal housing. Disposal in accordance with local regulations.

Triple Action Carpet & Upholstery Cleaner

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	2.1	See SP63	-	SP277	F-D,S-U	63 190 277 327 344 959	E0

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A145 A167 A802	E0
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Directive 75/734/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

Triple Action Carpet & Upholstery Cleaner

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : anionic surfactants
- less than 5 % : nonionic surfactants
- 5 % or over but less than 15 % : aliphatic hydrocarbons
- perfumes
- allergenic fragrances :
(r)-p-mentha-1,8-diene
citral

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Title for H, EUH and R indications mentioned in section 3 :

H220	Extremely flammable gas.
H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
R 12	Extremely flammable.
R 25	Toxic if swallowed.
R 36	Irritating to eyes.
R 50	Very toxic to aquatic organisms.
R 8	Contact with combustible material may cause fire.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS02 : Flame