

**BE110132 Mat Finish Plastic Protectant**

**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name : Mat Finish Plastic Protectant

Product code : BE110132

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

N/A

**1.3. Details of the supplier of the safety data sheet**

Registered company name : GS27

Address : Zac de la Liodière - 37300 Joué lès Tours FRANCE.

Telephone : 0033 247 737 788 Fax : 0033 247 670 012

www.gs27.com

**1.4. Emergency telephone number : +33 (0)1.45.42.59.59.**

Association/Organisation : INRS/ORFILA <http://www.centres-antipoison.net>.

**SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Flammable aerosol, Category 1 (Flam. Aerosol 1, H222).

May produce an allergic reaction (EUH208).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

**In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.**

Extremely flammable (F+, R 12).

May produce an allergic reaction.

Aquatic environmental hazard, chronic toxicity: harmful (R 52/53).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

**2.2. Label elements**

Detergent mixture (see section 15).

Mixture for spray application.

Mixture for aerosol application.

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS02

Signal Word :

DANGER

Additional labeling :

EUH208

Contains (R)-P-MENTHA-1,8-DIENE. May produce an allergic reaction.

EUH208

Contains CITRAL. May produce an allergic reaction.

**BE110132 Mat Finish Plastic Protectant**

Hazard statements :

H222 Extremely flammable aerosol.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.

Precautionary statements - Response :

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Precautionary statements - Storage :

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF.

Precautionary statements - Disposal :

P501 Dispose of contents/container to ...

Other information :

Récipient sous pression: peut éclater sous l'effet de la chaleur

**2.3. Other hazards**

The mixture does not contain any substances classified as 'Substances of Very High Concern' (SVHC) by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1. Substances**

No substances fulfil the criteria set forth in annexe II section A of the REACH regulation (EC) n° 1907/2006.

**3.2. Mixtures**

**Composition :**

Identification	(EC) 1272/2008	67/548/EEC	Note	%
CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32  BUTANE	GHS02, GHS04 Dgr Flam. Gas 1, H220	F+ F+;R12	C [1]	10 <= x % < 25
EC: 920-901-0 REACH: 01-2119456810-40  HYDROCARBONS, C11-C13, ISOALKANES, < 2% AROMATICS	GHS08 Dgr Asp. Tox. 1, H304 EUH:066	Xn Xn;R65 R66		2.5 <= x % < 10
CAS: 8042-47-5 EC: 232-455-8 REACH: 01-2119487078-27  HUILE MINÉRALE BLANCHE (PÉTROLE)	GHS08 Dgr Asp. Tox. 1, H304			1 <= x % < 2.5
INDEX: 601-029-00-7 CAS: 5989-27-5 EC: 227-813-5  (R)-P-MENTHA-1,8-DIENE	GHS02, GHS07, GHS09 Wng Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410 Aquatic Acute 1, H400	Xi,N Xi;R38-R43 N;R50/53 R10		0 <= x % < 1

**BE110132 Mat Finish Plastic Protectant**

INDEX: 605-019-00-3 CAS: 5392-40-5 EC: 226-394-6 REACH: 01-2119462829-23  CITRAL	GHS07 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317	Xi Xi;R38-R43		0 <= x % < 1
---	---	------------------	--	--------------

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

In the event of an allergic reaction, seek medical attention.

If inhaled, move the patient to fresh air and keep warm and at rest

**In the event of splashes or contact with eyes :**

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

**In the event of splashes or contact with skin :**

In the event of an allergic reaction, seek medical attention.

In case of irritation sensation, wash abundantly with water.

**In the event of swallowing :**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

---

**BE110132 Mat Finish Plastic Protectant**

---

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

Prevent every risk of ignition of the steams.

The pouring can bring the surfaces slippery.

**For non fire-fighters**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

**For fire-fighters**

Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

The elimination must be carried out by a registered salvage professional.

Use some absorbent.

**6.4. Reference to other sections**

No data available.

---

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Ensure that there is adequate ventilation, especially in confined areas.

Shake before using.

Prevent every contact with the skin and the eyes.

Use away of every flame or incandescent point.

Prevent accumulation of electrostatic charges.

Pulverise by short pressions, without prolonged pulverisation.

Follow hygiene and security rules because flammable capacity.

Do not pulverise towards a flame or an incandescent point.

Do not smoke.

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

---

**BE110132 Mat Finish Plastic Protectant**

---

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Keep the original packing. Do not pierce or burn even after use.

Follow the hygiene and security rules.

Rules of storage and manipulation applicables to the gaz under pressure.

Use only in well-ventilated premises.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

Do not use under tension.

Prevent high temperatures.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

---

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm	750 ppm	-	-	-

**8.2. Exposure controls**

**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

---

**BE110132 Mat Finish Plastic Protectant**

---

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

It's better to wear glasses in case of possible projections.

**- Hand protection**

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

- Natural latex

- PVC (polyvinyl chloride)

- Butyl Rubber (Isobutylene-isoprene copolymer)

Wearing gloves is recommended in case of frequent or prolonged contacts.

**- Body protection**

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Avoid every contact with the skin and the eyes. In case of contact, wash immediately with water during 10min.

**- Respiratory protection**

Do not use in closed and not ventilated space

Prevent any inhalation from the fog.

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : fluid liquid.  
spray.

**Important health, safety and environmental information**

pH : Not stated.  
neutral.

Boiling point/boiling range : 180 °C.

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density : < 1

Water solubility : Soluble.

Melting point/melting range : not specified.

Self-ignition temperature : 300 °C.

Decomposition point/decomposition range : 250 °C.

Chemical combustion heat : not specified.

Inflammation time : not specified.

Deflagration density : not specified.

Inflammation distance : not specified.

Flame height : not specified.

Flame duration : not specified.

**9.2. Other information**

No data available.

---

**BE110132 Mat Finish Plastic Protectant**

---

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- frost
- accumulation of electrostatic charges.
- flames and hot surfaces

**10.5. Incompatible materials**

Keep away from :

- strong oxidising agents
- strong acids

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

---

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

Splashes in the eyes may cause irritation and reversible damage

**11.1.1. Substances**

No toxicological data available for the substances.

**11.1.2. Mixture**

**Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

**Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 5989-27-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 5989-27-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity**

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

**BE110132 Mat Finish Plastic Protectant**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

Do not throw out product in the nature, in residual waters or superficial ones

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

Aerosol do not pierce or burn after use

CONSIGN TO AN APPROVED COLLECTOR. CONSULT THE PREFECTORAL ORDERS IN FORCE.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2011 - IMDG 2010 - ICAO/IATA 2012).

**14.1. UN number**

1950

**14.2. UN proper shipping name**

UN1950=AEROSOLS, flammable

**14.3. Transport hazard class(es)**

- Classification :



2.1

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	2.1	SP63	-	SP277	F-D,S-U	63 190 277 327 959	E0

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
------	-------	---------	----------	----------	----------	-------	-------	------	----



**BE110132 Mat Finish Plastic Protectant**

	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A145 A167 A802	E0
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Directive 2008/47/EC
- Regulation EC 1272/2008 modified by regulation EC 286/2011

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

**- Labelling for detergents (EC Regulation No. 648/2004, 907/2006) :**

- 30 % and more : aliphatic hydrocarbons
- perfumes
- allergenic fragrances :  
(r)-p-mentha-1,8-diene  
citral  
citronellol  
geraniol  
linalool

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.**

Hazard symbols :



Extremely flammable

Contains :

Contains 601-029-00-7 (R)-P-MENTHA-1,8-DIENE. May produce an allergic reaction.

**BE110132 Mat Finish Plastic Protectant**

---

Contains 605-019-00-3 CITRAL. May produce an allergic reaction.

Risk phrase :

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 12 Extremely flammable.

Safety phrase :

S 2 Keep away every burn , ignition source or spark - do not smoke.  
S 2 Keep out of the reach of children.  
S 46 If swallowed, seek medical advice immediately and show this container or label.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.  
Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.

S 51 Use only in well-ventilated areas.

S 23 Do not breathe the vapours.  
Pulverise by short pressions, without prolonged pulverisation.  
Do not use for any purpose other than the one for which it is intended.

**Title for H, EUH and R indications mentioned in section 3 :**

H220 Extremely flammable gas.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains <name of sensitising substance>. May produce an allergic reaction.  
R 10 Flammable.  
R 12 Extremely flammable.  
R 38 Irritating to skin.  
R 43 May cause sensitisation by skin contact.  
R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R 65 Harmful: may cause lung damage if swallowed.  
R 66 Repeated exposure may cause skin dryness or cracking.

**Abbreviations :**

ADR : European agreement concerning the international carriage of dangerous goods by Road.  
IMDG : International Maritime Dangerous Goods.  
IATA : International Air Transport Association.  
ICAO : International Civil Aviation Organisation  
RID : Regulations concerning the International carriage of Dangerous goods by rail.  
WGK : Wassergefahrdungsklasse (Water Hazard Class).  
GHS02 : Flame