


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 872380

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier

Trade name : SynPower™ SAE 5W-40
 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : lubricant

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
 Wieldrechtseweg 39
 3316 BG Dordrecht
 Netherlands
 +31 (0)78 654 3500 (in the Netherlands), or
 contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
 your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
 contact your local CSR contact person

SECTION 2: Hazards identification
2.1 Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements
Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

2.3 Other hazards
Additional advice

No information available.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 872380

SECTION 3: Composition/information on ingredients
3.2 Mixtures

Chemical nature : organic
 : Static Accumulator

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 25,00 - < 40,00
Reaction products of Benzeneamine, N- phenyl- with nonene (branched)	36878-20-3 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
Zinc bis[O-(6- methylheptyl)] bis[O- (sec-butyl)] bis(dithiophosphate)	93819-94-4 298-577-9 01-2119543726-33-xxxx	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic2; H411	>= 1,00 - < 2,50
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.
 If unconscious, place in recovery position and seek medical
 advice.
 If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get
 medical attention.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 872380

If on skin, rinse well with water.
 Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)

Risks : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures
5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO₂)
 Dry chemical


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
 nitrogen oxides (NOx)
 zinc oxide
 Sulphur oxides
 hydrogen sulfide
 mercaptans

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
 Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the
 application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national
 regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday. When
 using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated
 place.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection
8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls
Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below
 exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse
 effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : Nitrile rubber butyl-rubber

The suitability for a specific workplace should be discussed
 with the producers of the protective gloves.

Skin and body protection

: Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and
 concentration of the dangerous substance at the work place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH :
Not applicable

Pour point : < -39,00 °C

Boiling point/boiling range : > 225,00 °C

Flash point : 229 °C
Method: ASTM D 92

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0,01 hPa (25 °C)
Calculated Vapor Pressure


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

Relative vapour density	:	No data available
Relative density	:	0,853 (15,6 °C)
Density	:	0,855 g/cm ³ (15,6 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 13,4 - 14,4 mm ² /s (100 °C) ca. 85 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity
10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong bases


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 872380

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide and carbon monoxide
 hydrogen sulfide
 Nitrogen oxides (NOx)
 Sulphur oxides
 zinc oxide fumes
 mercaptans

SECTION 11: Toxicological information
11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
 Skin contact
 Eye Contact
 Ingestion

Acute toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: Not classified as acutely toxic by inhalation under GHS.
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
 Remarks: No mortality observed at this dose.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.
 Remarks: Information given is based on data obtained from similar substances.

Components:

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Acute oral toxicity : LD50 (Rat): 2.600 mg/kg


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg
 Method: OECD Test Guideline 402
 Assessment: Not classified as acutely toxic by dermal
 absorption under GHS.

Components:

C14-16-18 Alkyl phenol
 Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
 Assessment: Not classified as acutely toxic by ingestion under
 GHS.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
 Assessment: Not classified as acutely toxic by dermal
 absorption under GHS.
 Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based
 Species: Rabbit
 Result: No skin irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
 Species: Rabbit
 Result: Mild skin irritation
 Remarks: Information given is based on data obtained from similar substances.

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
 Species: Guinea pig
 Method: OECD Test Guideline 404
 Result: Irritating to skin.
 Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol
 Method: OECD Test Guideline 431
 Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes
 serious eye irritation.

Components:


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based
 Species: Rabbit
 Result: No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
 Species: Rabbit
 Result: Slight, transient irritation
 Remarks: Information given is based on data obtained from similar substances.

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
 Species: Rabbit
 Result: Corrosive
 Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol
 Species: Rabbit
 Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.
 Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.
 Remarks: Based on similar product.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based
 Test Type: Buehler Test
 Species: Guinea pig
 Assessment: Does not cause skin sensitisation.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
 Species: Guinea pig
 Assessment: Does not cause skin sensitisation.
 Method: OECD Test Guideline 406
 Remarks: Information given is based on data obtained from similar substances.


C14-16-18 Alkyl phenol
 Test Type: Local lymph node assay
 Species: Mouse
 Assessment: The product is a skin sensitiser, sub-category 1B.
 Method: OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
 Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium

	Page: 11
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 08.02.2018
	SDS Number: R0517099
SynPower™ SAE 5W-40 Synthetic Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 872380	Version: 2.4

Metabolic activation: with and without metabolic activation
 Result: negative

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
 Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

Genotoxicity in vivo : Test Type: Micronucleus test
 Test species: Mouse
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol
 Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 872380

SECTION 12: Ecological information
12.1 Toxicity
Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10.000 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: Calculated >= 1.000 mg/l
 Exposure time: 14 d
 Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL: 10 mg/l
 Exposure time: 21 d
 Species: Daphnia (water flea)
 Test substance: WAF
 Method: OECD Test Guideline 211

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
 Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

Test Type: static test
 Test substance: WAF

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
 Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4,5 mg/l
 Exposure time: 96 h
 Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Daphnia magna)): 5,4 mg/l
 Exposure time: 48 h
 Test Type: static test

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 2,1 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test

C14-16-18 Alkyl phenol
 Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test Type: static test
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF

12.2 Persistence and degradability

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based
 Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 0 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
 Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 1,5 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

C14-16-18 Alkyl phenol
 Biodegradability : Result: Readily biodegradable.
 Remarks: Expert judgement

12.3 Bioaccumulative potential
Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
 Partition coefficient: n- : log Pow: > 7,5
 octanol/water

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
 Partition coefficient: n- : log Pow: 0,59 - 1,2 (23 °C)
 octanol/water

C14-16-18 Alkyl phenol
 Partition coefficient: n- : log Pow: > 7,2
 octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects
Product:

Additional ecological : No data available
 information

SECTION 13: Disposal considerations
13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4

SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

Do not contaminate ponds, waterways or ditches with
 chemical or used container.
 Send to a licensed waste management company.

Contaminated packaging

: Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste
 handling site for recycling or disposal.
 Do not re-use empty containers.

SECTION 14: Transport information
SECTION 14: Transport information**14.1 UN number**

ADR: Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** Not dangerous goods**INTERNATIONAL MARITIME DANGEROUS GOODS:** Not dangerous goods

RID: Not dangerous goods

14.2 UN proper shipping name

ADR: Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** Not dangerous goods**INTERNATIONAL MARITIME DANGEROUS GOODS:** Not dangerous goods

RID: Not dangerous goods

14.3 Transport hazard class(es)

ADR: Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** Not dangerous goods**INTERNATIONAL MARITIME DANGEROUS GOODS:** Not dangerous goods

RID: Not dangerous goods


14.4 Packing group

ADR: Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:** Not dangerous goods**INTERNATIONAL MARITIME DANGEROUS GOODS:** Not dangerous goods

RID: Not dangerous goods

14.5 Environmental hazards

		Page: 16
SAFETY DATA SHEET		Revision Date: 11.01.2017
		Print Date: 08.02.2018
		SDS Number: R0517099
SynPower™ SAE 5W-40 Synthetic Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 872380		Version: 2.4

ADR: Not applicable

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not applicable

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not applicable

INTERNATIONAL MARITIME DANGEROUS GOODS: Not applicable

RID: Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Ship Type: Not applicable

Hazard code(s): Not applicable

Pollutant Category: Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable


REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

		Page: 17
SAFETY DATA SHEET		Revision Date: 11.01.2017
		Print Date: 08.02.2018
		SDS Number: R0517099
SynPower™ SAE 5W-40 Synthetic Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 872380		Version: 2.4

- DSL : All components of this product are on the Canadian DSL
- AICS On the inventory, or in compliance with the inventory
- ENCS On the inventory, or in compliance with the inventory
- KECI On the inventory, or in compliance with the inventory
- PICCS On the inventory, or in compliance with the inventory
- IECSC On the inventory, or in compliance with the inventory
- TSCA On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Revision Date: 11.01.2017

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318** Causes serious eye damage.
- H373** May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H413** May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).


SAFETY DATA SHEET

Revision Date: 11.01.2017

Print Date: 08.02.2018

SDS Number: R0517099

Version: 2.4


SynPower™ SAE 5W-40 Synthetic Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 872380

Sources of key data used to compile the Safety Data Sheet
 Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling
 (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data
 sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
 ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN: Regulation for the Carriage of Dangerous Substances on the Rhine
 CLP : Classification, Labelling and Packaging

	Page: 19
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 08.02.2018
	SDS Number: R0517099
SynPower™ SAE 5W-40 Synthetic Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 872380	Version: 2.4

- CSA : Chemical Safety Assessment
- CSR : Chemical Safety Report
- DNEL : Derived No Effect Level.
- EINECS : European Inventory of Existing Commercial Chemical Substances.
- ELINCS : European List of Notified Chemical Substances
- PEC : Predicted Effect Concentration
- PEL : Permissible Exposure Limits
- PNEC : Predicted No Effect Concentration
- R-phrase : Risk phrase
- REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
- RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
- S-phrase: Safety phrase
- WGK : German Water Hazard Class