		Page: 1
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Synpower™ POWER ST.FL
Power Steering Fluid

1.2 Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Hydraulic oil

1.3 Details of the supplier of the safety data sheet Ellis Enterprises B.V., an affiliate of Valvoline Wieldrechtseweg 39 3316 BG Dordrecht Netherlands SDS@valvoline.com	1.4 Emergency telephone number 00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112 Product Information +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
---	---

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters airways.


2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :  

Signal word : Danger

Hazard statements : H304 May be fatal if swallowed and enters airways.

		
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

	H332	Harmful if inhaled.
Precautionary statements	: P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	Prevention:	
	P271	Use only outdoors or in a well-ventilated area.
	Response:	
	P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Do NOT induce vomiting.
	P331	
	Storage:	
	P405	Store locked up.
	Disposal:	
	P501	Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

1-DECENE, DIMER, HYDROGENATED

White mineral oil

2.3 Other hazards

Additional advice

No information available.


SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
1-DECENE, DIMER, HYDROGENATED	68649-11-6 01-2119493069-28-xxxx	Acute Tox.4; H332 Asp. Tox.1; H304	>= 70 - < 80
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based	72623-86-0 276-737-9	Asp. Tox.1; H304	>= 15 - < 25
White mineral oil	8042-47-5 232-455-8	Asp. Tox.1; H304	>= 2,5 - < 5

For explanation of abbreviations see section 16.

		Page: 3
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		


SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
IF INHALED: Call a POISON CENTER or doctor/ physician if you feel unwell.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
- Risks : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current

		Page: 4
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

workplace exposure limits is unlikely to cause pulmonary abnormalities.
 May be fatal if swallowed and enters airways.
 Harmful if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
 Do not allow run-off from fire fighting to enter drains or water courses.


Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 Hydrogen chloride gas

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

		Page: 5
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
 Ensure adequate ventilation.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
 Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.


SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

		Page: 6
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.


Hand protection

Remarks : Nitrile rubber

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:
 impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.


Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

		Page: 7
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: dark green
Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: -60 °C
	No data available
Boiling point/boiling range	: > 300 °C
Flash point	: 160 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6,5 %(V)
Lower explosion limit	: 0,6 %(V)
Vapour pressure	: < 0,001 hPa
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0,825 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 235 °C

		
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : 19 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid


Conditions to avoid : excessive heat
Exposure to sunlight.

10.5 Incompatible materials

Materials to avoid : Iron
steel
Strong acids
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons
Hydrogen chloride gas

		
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Harmful if inhaled.

Components:

1-DECENE, DIMER, HYDROGENATED:

Acute oral toxicity : LD 50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): > 1,81 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The component/mixture is classified as acute inhalation toxicity, category 4.

Acute dermal toxicity : LD 50 (Rabbit): > 3.000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Components:

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD 50 (Rat): > 5.000 mg/kg

Components:

Mineral Oil:

Acute oral toxicity : LD 50 (Rat): 50.000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.


Skin corrosion/irritation

Not classified based on available information.

Components:

1-DECENE, DIMER, HYDROGENATED:

Species: Rabbit

		Page: 10
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

Result: Slightly irritating to skin

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: Not irritating to skin

Mineral Oil:

Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

1-DECENE, DIMER, HYDROGENATED:

Species: Rabbit

Result: Not irritating to eyes

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: Not irritating to eyes

Mineral Oil:

Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

1-DECENE, DIMER, HYDROGENATED:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Method: OECD Test Guideline 406

Germ cell mutagenicity


Not classified based on available information.

Components:

1-DECENE, DIMER, HYDROGENATED:

Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative
 GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test

		Page: 11
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

Test species: Mouse
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

1-DECENE, DIMER, HYDROGENATED:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Mineral Oil:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.


SECTION 12: Ecological information

12.1 Toxicity

Components:

1-DECENE, DIMER, HYDROGENATED

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF

		Page: 12
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
Synpower™ POWER ST.FL Power Steering Fluid		SDS Number: 000000197928
VE18320		Version: 1.3

Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : EL50 (Scenedesmus capricornutum (fresh water algae)): > 1.000 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201
GLP: yes

12.2 Persistence and degradability

Components:

1-DECENE, DIMER, HYDROGENATED

Biodegradability : Result: Inherently biodegradable
Biodegradation: 15 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: The bioaccumulation potential cannot be determined.

Components:

1-DECENE, DIMER, HYDROGENATED

Partition coefficient: n-octanol/water : log Pow: > 6,5

12.4 Mobility in soil


No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

Product:

		Page: 13
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14: Transport information

SECTION 14: Transport information

14.1 UN number


ADR:
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:
INTERNATIONAL MARITIME DANGEROUS GOODS:
RID:

14.2 UN proper shipping name

ADR:
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:
INTERNATIONAL MARITIME DANGEROUS GOODS:
RID:

14.3 Transport hazard class(es)

ADR:
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:
INTERNATIONAL MARITIME DANGEROUS GOODS:
RID:

		Page: 14
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

14.4 Packing group

ADR:

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:

INTERNATIONAL MARITIME DANGEROUS GOODS:

RID:

14.5 Environmental hazards

ADR: Not applicable

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not applicable

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not applicable

RID: Not applicable

: Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Ship Type: Not applicable

Hazard code(s): Not applicable

Pollutant Category: Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture


REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 57) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Page: 15
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

Not applicable

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL All components of this product are on the Canadian DSL.

AUSTR On the inventory, or in compliance with the inventory

ENCS Not in compliance with the inventory

KECL On the inventory, or in compliance with the inventory

IECSC Not in compliance with the inventory

PICCS Not in compliance with the inventory

NZ CLSC

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

15.2 Chemical Safety Assessment

No data available

SECTION 16: Other information

Further information

Revision Date: 31.07.2016


Full text of H-Statements referred to under sections 2 and 3.

H304 May be fatal if swallowed and enters airways.

H332 Harmful if inhaled.

Further information

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

		Page: 16
SAFETY DATA SHEET		Revision Date: 31.07.2016
		Print Date: 18.09.2017
		SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid		Version: 1.3
VE18320		

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands

ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine


CLP : Classification, Labelling and Packaging

CSA : Chemical Safety Assessment

CSR : Chemical Safety Report

DNEL : Derived No Effect Level.

EINECS : European Inventory of Existing Commercial Chemical Substances.

	Page: 17
SAFETY DATA SHEET	Revision Date: 31.07.2016
	Print Date: 18.09.2017
	SDS Number: 000000197928
Synpower™ POWER ST.FL Power Steering Fluid VE18320	Version: 1.3

ELINCS : European List of Notified Chemical Substances

PEC : Predicted Effect Concentration

PEL : Permissible Exposure Limits

PNEC : Predicted No Effect Concentration

R-phrase : Risk phrase

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK : German Water Hazard Class