


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887047

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier

Trade name : Valvoline™ WHITE GREASE

™ Trademark, Valvoline or its subsidiaries, registered in various countries

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricant

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
 Wieldrechtseweg 39
 3316 BG Dordrecht
 Netherlands
 +31 (0)78 654 3500 (in the Netherlands), or
 contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
 your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
 contact your local CSR contact person

SECTION 2: Hazards identification
2.1 Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.


H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single
 exposure, Category 3, Central nervous
 system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard,
 Category 2

H411: Toxic to aquatic life with long lasting effects.

	
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 14.02.2019
	SDS Number: 000000274772
Valvoline™ WHITE GREASE ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887047	Version: 1.0

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P102 Keep out of reach of children.
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
P501 Dispose of contents/container in accordance with regional regulations.

Hazardous components which must be listed on the label:

Pentane

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887047

3.2 Mixtures
Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Pentane	109-66-0 203-692-4 01-2119459286-30-xxxx	Flam. Liq.1; H224 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 40,00 - < 50,00
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0 01-2119473851-33-xxxx	Flam. Liq.2; H225 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 10,00 - < 15,00
Substances with a workplace exposure limit :			
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 10,00 - < 15,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move out of dangerous area.
 Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : Move to fresh air.
 If unconscious, place in recovery position and seek medical advice.
 Consult a physician after significant exposure.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887047

Remove contact lenses.
 Protect unharmed eye.
 If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : May cause drowsiness or dizziness.
 Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures
5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray
 Foam
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887047

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
 Remove all sources of ignition.
 Ensure adequate ventilation.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
 Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up
6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Open drum carefully as content may be under pressure.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887047

Take precautionary measures against static discharges.
 Avoid exposure - obtain special instructions before use.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Pentane	109-66-0	TWA	1.000 ppm 3.000 mg/m ³	2006/15/EC
		TWA	600 ppm 1.800 mg/m ³	GB EH40
Butane	106-97-8	STEL	750 ppm 1.810 mg/m ³	GB EH40
		TWA	600 ppm 1.450 mg/m ³	GB EH40


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887047

8.2 Exposure controls
Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Flame-resistant clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
 In the case of dust or aerosol formation use respirator with an approved filter.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : white, translucent

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 887047

Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	10,9 %(V)
Lower explosion limit / Lower flammability limit	:	0,6 %(V)
Vapour pressure	:	8 hPa (20 °C)
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0,67 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity
10.1 Reactivity

No decomposition if stored and applied as directed.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 00000274772

Version: 1.0

Valvoline™ WHITE GREASE

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887047

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

Heat, flames and sparks.

10.5 Incompatible materials

 Materials to avoid : Acids
 Alkali metals
 Amines
 Oxidizing agents
 strong bases
 strong reducing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information
11.1 Information on toxicological effects

 Information on likely routes of exposure : Inhalation
 Skin contact
 Eye Contact
 Ingestion


Acute toxicity

Not classified based on available information.

Components:
PENTANE NORMAL:

 Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
 Assessment: Not classified as acutely toxic by ingestion under GHS.
 Remarks: No mortality observed at this dose.

 Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
 Exposure time: 4 h

	Page: 10
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 14.02.2019
	SDS Number: 000000274772
Valvoline™ WHITE GREASE ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887047	Version: 1.0

Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat, male and female): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 23,3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rat, male and female): > 2.800 - 3.100 mg/kg

Components:

BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l
Exposure time: 2 h

LC50 (Rat): > 50000 ppm
Exposure time: 2 h
Test atmosphere: gas

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

PENTANE NORMAL:

Result: Slight, transient irritation

Result: Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887047

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:**PENTANE NORMAL:**

Result: Slight, transient irritation

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:**

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:**

Genotoxicity in vitro

: Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

: Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo

: Test Type: In vivo micronucleus test

Test species: Mouse

Application Route: Oral


Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity-
Assessment: Classified based on benzene content < 0.1% (Regulation (EC)
1272/2008, Annex VI, Part 3, Note P)**BUTANE NORMAL:**

Genotoxicity in vitro

: Test Type: Ames test

	Page: 12
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 14.02.2019
	SDS Number: 000000274772
Valvoline™ WHITE GREASE ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887047	Version: 1.0

Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)
Assessment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

PENTANE NORMAL:

Assessment: May cause drowsiness or dizziness.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

PENTANE NORMAL:

May be fatal if swallowed and enters airways.


Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

		Page: 13
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 14.02.2019
		SDS Number: 000000274772
Valvoline™ WHITE GREASE ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887047		Version: 1.0

SECTION 12: Ecological information

12.1 Toxicity

Components:

Pentane

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 10,7 mg/l
Exposure time: 72 h

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 3 - 10 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4,6 - 10 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,17 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment
Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

Butane



SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887047

- Toxicity to fish : Remarks: No toxicity at the limit of solubility
 QSAR
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100 mg/l
 Exposure time: 48 h
 Remarks: QSAR
- Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l
 Exposure time: 96 h
 Remarks: QSAR

12.2 Persistence and degradability

Components:

- Pentane
 Biodegradability : Result: Readily biodegradable.
 Biodegradation: 87 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F
- Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
 Biodegradability : Inoculum: activated sludge
 Biodegradation: 98 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F
 Remarks: Information given is based on data obtained from similar substances.
- Butane
 Biodegradability : Result: Readily biodegradable.
 Remarks: Information given is based on data obtained from similar substances.


12.3 Bioaccumulative potential

Components:

- Pentane
 Partition coefficient: n-octanol/water : log Pow: 3,39
- Butane
 Partition coefficient: n-octanol/water : log Pow: 2,89

12.4 Mobility in soil

No data available

		Page: 15
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 14.02.2019
		SDS Number: 000000274772
Valvoline™ WHITE GREASE ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887047		Version: 1.0

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS

SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 00000274772

Version: 1.0

Valvoline™ WHITE GREASE
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 887047

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN
 Packing group : Not assigned by regulation
 Classification Code : 5F
 Labels : 2.1

ADR
 Packing group : Not assigned by regulation
 Classification Code : 5F
 Labels : 2.1
 Tunnel restriction code : (D)

RID
 Packing group : Not assigned by regulation
 Classification Code : 5F
 Hazard Identification Number : 23
 Labels : 2.1

IMDG
 Packing group : Not assigned by regulation
 Labels : 2.1
 EmS Code : F-D, S-U

IATA (Cargo)
 Packing instruction (cargo aircraft) : 203
 Packing instruction (LQ) : Y203
 Packing group : Not assigned by regulation
 Labels : Flammable gas

IATA (Passenger)
 Packing instruction (passenger aircraft) : 203
 Packing instruction (LQ) : Y203


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 887047

Packing group : Not assigned by regulation
 Labels : Flammable gas

14.5 Environmental hazards
ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that : Not applicable
 deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic : Not applicable
 pollutants

REACH - List of substances subject to authorisation : Not applicable
 (Annex XIV)

REACH - Restrictions on the manufacture, placing on : Not applicable
 the market and use of certain dangerous substances,
 preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High : Not applicable
 Concern for Authorisation (Article 57).

**SAFETY DATA SHEET**

Revision Date: 17.10.2018

Print Date: 14.02.2019

SDS Number: 000000274772

Version: 1.0

Valvoline™ WHITE GREASE

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887047

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Other regulations : Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.

AICS Not in compliance with the inventory

ENCS Not in compliance with the inventory

KECI Not in compliance with the inventory

PICCS Not in compliance with the inventory

IECSC Not in compliance with the inventory

TCSI Not in compliance with the inventory


TSCA Not On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

		Page: 19
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 14.02.2019
		SDS Number: 000000274772
Valvoline™ WHITE GREASE ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887047		Version: 1.0

SECTION 16: Other information

Further information

Revision Date: 17.10.2018

Full text of H-Statements

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade


GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

	Page: 20
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 14.02.2019
	SDS Number: 000000274772
Valvoline™ WHITE GREASE ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887047	Version: 1.0

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands

ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP : Classification, Labelling and Packaging

CSA : Chemical Safety Assessment

CSR : Chemical Safety Report

DNEL : Derived No Effect Level.

EINECS : European Inventory of Existing Commercial Chemical Substances.

ELINCS : European List of Notified Chemical Substances

PEC : Predicted Effect Concentration

PEL : Permissible Exposure Limits

PNEC : Predicted No Effect Concentration

R-phrase : Risk phrase

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK : German Water Hazard Class