


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887063

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier

Trade name : Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Cleaner.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
 Wieldrechtseweg 39
 3316 BG Dordrecht
 Netherlands
 +31 (0)78 654 3500 (in the Netherlands), or
 contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
 your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
 contact your local CSR contact person

SECTION 2: Hazards identification
2.1 Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Long-term (chronic) aquatic hazard,
 Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements
Labelling (REGULATION (EC) No 1272/2008)



SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887063

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H222
H229
H412

Extremely flammable aerosol.
 Pressurised container: May burst if heated.
 Harmful to aquatic life with long lasting effects.

Precautionary statements

: P102
Prevention:
P210

P211

P251
P260
Storage:
P410 + P412

Keep out of reach of children.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe spray.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501

Dispose of contents/container in accordance with regional regulations.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Hydrocarbons, C9, aromatics	64742-95-6 918-668-5	Flam. Liq.3; H226 STOT SE3; H336	>= 5,00 - < 10,00


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

		STOT SE3; H335 Asp. Tox.1; H304 Aquatic Chronic2; H411	
Substances with a workplace exposure limit :			
dimethoxymethane	109-87-5 01-2119664781-31-xxxx	Flam. Liq.2; H225	>= 70,00 - < 80,00
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 5,00 - < 10,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures
5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray

Foam

Alcohol-resistant foam

Carbon dioxide (CO₂)

Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

 Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.

 Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

 Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
 Remove all sources of ignition.
 Ensure adequate ventilation.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
 Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up
6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Open drum carefully as content may be under pressure.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not smoke.
 Container hazardous when empty.
 Take precautionary measures against static discharges.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.
 Container may be opened only under exhaust ventilation hood.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday.


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethoxymethane	109-87-5	TWA	1.000 ppm 3.160 mg/m ³	GB EH40
		STEL	1.250 ppm 3.950 mg/m ³	GB EH40
Butane	106-97-8	STEL	750 ppm 1.810 mg/m ³	GB EH40
		TWA	600 ppm 1.450 mg/m ³	GB EH40

8.2 Exposure controls
Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection

Remarks : The suitability for a specific workplace should be discussed


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Flame-resistant clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : white, translucent

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : 19,9 %(V)

Lower explosion limit / Lower flammability limit : 1,7 %(V)

Vapour pressure : 3.500 hPa (20 °C)

Relative vapour density : No data available

Relative density : No data available

Density : 0,75 g/cm³ (20 °C)


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Ignition temperature : 235 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity
10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information
11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:
Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 (Rat, female): 3.492 mg/kg

LD50 (Rat, male): 6.984 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg

Components:
BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l
Exposure time: 2 h

LC50 (Rat): > 50000 ppm
Exposure time: 2 h
Test atmosphere: gas

Skin corrosion/irritation

Not classified based on available information.

Components:
Hydrocarbons, C9, aromatics:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Slight, transient irritation


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 00000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:
Hydrocarbons, C9, aromatics:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:
Hydrocarbons, C9, aromatics:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:
Hydrocarbons, C9, aromatics:

 Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
 Result: negative

 Germ cell mutagenicity-
 Assessment : Classified based on benzene content < 0.1% (Regulation (EC)
 1272/2008, Annex VI, Part 3, Note P)

BUTANE NORMAL:


 Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

Carcinogenicity

Not classified based on available information.

Components:
Hydrocarbons, C9, aromatics:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)

		Page: 11
SAFETY DATA SHEET		Revision Date: 01.10.2018
		Print Date: 14.02.2019
		SDS Number: 000000274828
Valvoline™ GASKET REMOVER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887063		Version: 1.0

Assessment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information


12.1 Toxicity

Components:

Hydrocarbons, C9, aromatics

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): 3,2 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

		Page: 12
SAFETY DATA SHEET		Revision Date: 01.10.2018
		Print Date: 14.02.2019
		SDS Number: 000000274828
Valvoline™ GASKET REMOVER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887063		Version: 1.0

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,9 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

NOEL (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Butane
Toxicity to fish : Remarks: No toxicity at the limit of solubility
QSAR

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100 mg/l
Exposure time: 48 h
Remarks: QSAR

Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l
Exposure time: 96 h
Remarks: QSAR

12.2 Persistence and degradability

Components:

Butane
Biodegradability : Result: Readily biodegradable.
Remarks: Information given is based on data obtained from similar substances.


12.3 Bioaccumulative potential

Components:

Butane
Partition coefficient: n-octanol/water : log Pow: 2,89

12.4 Mobility in soil

No data available

		Page: 13
SAFETY DATA SHEET		Revision Date: 01.10.2018
		Print Date: 14.02.2019
		SDS Number: 000000274828
Valvoline™ GASKET REMOVER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887063		Version: 1.0

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS

SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 00000274828

Version: 1.0

Valvoline™ GASKET REMOVER
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 887063

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN
 Packing group : Not assigned by regulation
 Classification Code : 5F
 Labels : 2.1

ADR
 Packing group : Not assigned by regulation
 Classification Code : 5F
 Labels : 2.1
 Tunnel restriction code : (D)

RID
 Packing group : Not assigned by regulation
 Classification Code : 5F
 Hazard Identification Number : 23
 Labels : 2.1

IMDG
 Packing group : Not assigned by regulation
 Labels : 2.1
 EmS Code : F-D, S-U

IATA (Cargo)
 Packing instruction (cargo aircraft) : 203
 Packing instruction (LQ) : Y203
 Packing group : Not assigned by regulation
 Labels : Flammable gas

IATA (Passenger)
 Packing instruction (passenger aircraft) : 203
 Packing instruction (LQ) : Y203


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 887063

Packing group : Not assigned by regulation
 Labels : Flammable gas

14.5 Environmental hazards
ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that : Not applicable
 deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic : Not applicable
 pollutants

REACH - List of substances subject to authorisation : Not applicable
 (Annex XIV)

REACH - Restrictions on the manufacture, placing on : Not applicable
 the market and use of certain dangerous substances,
 preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High : Not applicable
 Concern for Authorisation (Article 57).


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887063

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Other regulations : Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL	: This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.
AICS	Not in compliance with the inventory
ENCS	Not in compliance with the inventory
KECI	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory
TCSI	Not in compliance with the inventory
TSCA	Not On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

		Page: 17
SAFETY DATA SHEET		Revision Date: 01.10.2018
		Print Date: 14.02.2019
		SDS Number: 000000274828
Valvoline™ GASKET REMOVER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887063		Version: 1.0

Further information

Revision Date: 01.10.2018

Full text of H-Statements

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"


SAFETY DATA SHEET

Revision Date: 01.10.2018

Print Date: 14.02.2019

SDS Number: 000000274828

Version: 1.0

Valvoline™ GASKET REMOVER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887063

IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
 ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN: Regulation for the Carriage of Dangerous Substances on the Rhine
 CLP : Classification, Labelling and Packaging
 CSA : Chemical Safety Assessment
 CSR : Chemical Safety Report
 DNEL : Derived No Effect Level.
 EINECS : European Inventory of Existing Commercial Chemical Substances.
 ELINCS : European List of Notified Chemical Substances
 PEC : Predicted Effect Concentration
 PEL : Permissible Exposure Limits
 PNEC : Predicted No Effect Concentration
 R-phrase : Risk phrase
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
 S-phrase: Safety phrase
 WGK : German Water Hazard Class