



## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

#### SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1. Product identifier

Product name : BAR'S LEAKS RADIATOR STOP LEAK  
Product code : RSC1L

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU21 Consumer product. PC0 Other. Engine maintenance.

##### 1.3. Details of the supplier of the safety data sheet

Supplier : Bar's Products Europe, B.V.  
Westelijk Halfmond 487  
1183 JD Amstelveen, The Netherlands

Telephone : +31-20-7989301  
Fax : +31-20-7989302  
E-mail : Info@barseurope.com  
Website : www.barseurope.com

Supplier : Bar's Products International, Ltd.  
1510 W. 135th  
90249 Gardena, CA, United States of America

Telephone : +01 310 5155096

##### 1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

NL - Telephone : +31-20-7989301

(During office hours only)

EMERGENCY TELEPHONE NUMBER (for DOCTORS only):

(24/7)

#### SECTION 2 HAZARDS IDENTIFICATION

##### 2.1. Classification of the substance or mixture

CLP classification (1272/2008/EC) : Acute toxicity, category 4. Skin sensitization, category 1. Specific target organ toxicity — repeated exposure, category 2.

Human health hazards : Harmful if swallowed. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure.

Physical/chemical hazards : Not classified as dangerous according to statutory EC-Directives.

Environmental hazards : Not classified as dangerous according to statutory EC-Directives.

Other information : Keep out of the reach of children.

##### 2.2. Label elements

Label elements (1272/2008/EC):

Hazard pictograms :



Signal word : Warning



## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

H- and P-phrases	: H302	Harmful if swallowed.
	H317	May cause an allergic skin reaction.
	H373	May cause damage to organs through prolonged or repeated exposure.
	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P260 vapour	Do not breathe vapours.
	P270	Do not eat, drink or smoke when using this product.
	P280 gloves	Wear protective gloves.
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
	P302+P352	IF ON SKIN: Wash with plenty of water/soap.
	P314	Get medical advice/attention if you feel unwell.
	P501	Dispose of contents/container to an official chemical waste depot.

#### Additional labelling (for all packaging sizes)

- : Contains: Ethane-1,2-diol ; 2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol .
- : 3 per cent of the mixture consists of component(s) of unknown acute toxicity.

Other information : According to Regulation (EC) No 1272/2008, the packaging of this product shall carry a tactile warning of danger.

#### 2.3. Other hazards

Other information : Does not contain PBT or vPvB substances.

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

Product description : Mixture.

Information on hazardous substances:

Substance name	Concentration (w/w) (%)	CAS nr.	EC number	Remark	REACH nr.
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	0,1 - < 1	4719-04-4	225-208-0		
Sodium carbonate	0,1 - < 1	497-19-8	207-838-8		
Curcumin	1 - < 5	458-37-7	207-280-5		
Ethane-1,2-diol	25 - 50	107-21-1	203-473-3		

Substance name	Hazard Class	H-phrases	Pictograms	
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	Acute Tox. 4; Acute Tox. 2; Skin Sens. 1; STOT RE 1	H302; H330; H317; H372	GHS06; GHS07; GHS08	H317 : C ≥ 0.1 %
Sodium carbonate	Eye Irrit. 2	H319	GHS07	
Curcumin	Skin Irrit. 2; Eye Irrit. 2; STOT SE 3	H315; H319; H335	GHS07	
Ethane-1,2-diol	Acute Tox. 4; STOT RE 2	H302; H373	GHS07; GHS08	

Occupational exposure limit(s), if relevant, are listed in section 8.

Reference is made to chapter 16 for full text of each relevant H phrase.

## SECTION 4 FIRST-AID MEASURES

#### 4.1. Description of first aid measures

Product name : Bar's Leaks Radiator Stop Leak  
Date of issue : 10-11-2015 Replaces issue dated : ---

Page 2/10  
INFO CARE SDS



## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

#### First aid measures

- Inhalation : Move victim into fresh air. Consult a doctor if victim feels unwell.
- Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up. Consult a doctor if irritation occurs.
- Eye contact : Wash out with (lukewarm) water for at least 15 minutes. Remove contact lenses. Consult a doctor if irritation persists.
- Ingestion : Do not induce vomiting. Do rinse the mouth. Give one glass of water. Never give anything by mouth to an unconscious person. Consult a doctor immediately if victim feels unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### Effects and symptoms

- Inhalation : May cause headache, dizziness and a feeling of sickness.
- Skin contact : May cause redness and irritation, sensitisation. May produce an allergic reaction. May cause dry skin.
- Eye contact : May cause stinging of eyes and redness.
- Ingestion : May cause a feeling of sickness, vomiting and diarrhoea. May cause a feeling of sickness, malaise, shortness of breath and lack of breathe.

#### 4.3. Indication of any immediate medical attention and special treatment needed

- Note to physicians :
- General : Risk of metabolic acidosis.

## SECTION 5 FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing media

##### Extinguishing media

- Suitable : Carbondioxide (CO2). Alcohol resistant foam. Dry chemical. Water fog.
- Not suitable : None known.

#### 5.2. Special hazards arising from the substance or mixture

- Special exposure hazards : None known.
- Hazardous thermal decomposition products : Carbon monoxide may be evolved if incomplete combustion occurs.

#### 5.3. Advice for firefighters

- Special protective equipment for fire-fighters : Use adequate respiratory equipment in case of insufficient ventilation.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

- Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with spilled or released material. Vapours are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

#### 6.2. Environmental precautions

- Environmental precautions : Avoid release of product into sewers, surface water and/or ground water. In case of large spills: contain with dike.
- Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.



## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Dispose at an authorised waste collection point. Wash away remainder with plenty of water and soap.

#### 6.4. Reference to other sections

Reference to other sections : See also section 8.

## SECTION 7 HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Do not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep in a cool, dry and well-ventilated place (< 35 °C). Keep away from oxidizing agents. Keep away from food, drink and animal feedingstuffs.

Recommended packaging : Keep only in the original container.

Non recommended packaging : Steel (except stainless steel).

#### 7.3. Specific end use(s)

Use : Use only as directed.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Occupational exposure limits : Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have not been established for this product.

Workplace exposure limits (mg/m<sup>3</sup>):

Chemical name	Country	TWA 8 hour (mg/m <sup>3</sup> )	STEL 15 min (mg/m <sup>3</sup> )	Comments
Sodium carbonate		1	3	
Ethane-1,2-diol	GB	52	104	Skin
Ethane-1,2-diol	EC	52	104	Skin

Derived no-effect level (DNEL) for workers:

Chemical name	Route of exposure	DNEL, short-term		DNEL, long-term	
		Local effect	Systemic effect	Local effect	Systemic effect
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	Inhalation			0,2 mg/m <sup>3</sup>	
Sodium carbonate	Inhalation			10 mg/m <sup>3</sup>	
Ethane-1,2-diol	Dermal				106 mg/kg bw/day
	Inhalation			35 mg/m <sup>3</sup>	

Derived no-effect level (DNEL) for consumers:

Chemical name	Route of exposure	DNEL, short-term		DNEL, long-term	
		Local effect	Systemic effect	Local effect	Systemic effect

Product name : Bar's Leaks Radiator Stop Leak

Date of issue : 10-11-2015

Replaces issue dated : ---

Page 4/10

INFO CARE SDS



## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

Sodium carbonate	Inhalation	10 mg/m <sup>3</sup>			
Ethane-1,2-diol	Dermal				53 mg/kg bw/day
	Inhalation			7 mg/m <sup>3</sup>	

Predicted no-effect concentration (PNEC):

Chemical name	Route of exposure	Fresh water	Marine water	
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	Water	0,0066 mg/l	0,00066 mg/l	
	Sediment	0,0304 mg/kg	0,00304 mg/kg	
	Intermittent water			0,066 mg/l
Ethane-1,2-diol	STP			5,5 mg/l
	Soil			0,00219 mg/kg
	Water	10 mg/l	1 mg/l	
	Sediment	20,9 mg/kg		
	Intermittent water			10 mg/l
	STP			199,5 mg/l
	Soil			1,53 mg/kg

#### 8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.



Body protection : Wear appropriate protective clothing, overalls or suit, and similar boots in accordance with EN 365/367 resp. 345. Suitable material: nitril. Indication of permeation breakthrough time: 6 hours.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance with EN 140.

Hand protection : Wear appropriate safety gloves in accordance with EN 374. Suitable material: nitril. ± 0,5 mm. Indication of permeation breakthrough time: 6 hours.

Eye protection : Wear appropriate safety glasses when there is danger of possible eye contact.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance : Liquid.

Colour : Green.

Odour : Characteristic.

Odour threshold : Not known.

pH : 2 - 11,5

Solubility in water : Dispersible.

Partition coefficient : Not known.

(n-octanol/water)

Flash point : > 100 °C

Flammability (solid, gas) : Not applicable. Liquid. See flashpoint.

Auto ignition temperature : > 398 °C



## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

Boiling point/boiling range	: 100 °C	
Melting point/melting range	: -23 °C	
Explosive properties	: None known.	Does not contain explosives.
Explosion limits (% in air)	: Not known.	Lower explosion limit in air (%): 3,2 ( Ethane-1,2-diol )
	:	Upper explosion limit in air (%): 15,3
Oxidising properties	: Not applicable.	Does not contain oxidizing substances.
Decomposition temperature	: Not applicable.	
Viscosity (20°C)	: Not known.	
Viscosity (40°C)	: Not relevant.	The product contains < 10% substances having an aspiration hazard.
Vapour pressure (20°C)	: Not known.	
Vapour density (20°C)	: > 1	(air = 1)
Relative density (20°C)	: 1 g/ml	
Evaporation rate	: < 1	(n-butyl acetate = 1)

## SECTION 10 STABILITY AND REACTIVITY

### 10.1. Reactivity

Reactivity : See sub-sections below.

### 10.2. Chemical stability

Stability : Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

### 10.4. Conditions to avoid

Conditions to avoid : See section 7.

### 10.5. Incompatible materials

Materials to avoid : Keep away from oxidizing agents.

### 10.6. Hazardous decomposition products

Hazardous decomposition products : Not known.

## SECTION 11 TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

No toxicological research has been carried out on this product.

#### Inhalation

Acute toxicity	: Calculated LC50: > 5,679 mg/l. Ingredients of unknown toxicity: 15 %. ATE: > 5 mg/l. Low toxicity. Not classified - based on available data, the classification criteria are not met. May cause headache, dizziness and a feeling of sickness.
Corrosion/irritation	: Not classified - based on available data, the classification criteria are not met.
Sensitisation	: Does not contain substances classified as respiratory sensitiser. Not classified - based on available data, the classification criteria are not met.
Carcinogenicity	: Not classified - based on available data, the classification criteria are not met.
Mutagenicity	: Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.

#### Skin contact



# Safety data sheet

According to Regulation (EU) No 453/2010

## Bar's Leaks Radiator Stop Leak

- Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: 5 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
- Corrosion/irritation : Not classified - based on available data, the classification criteria are not met.
- Sensitisation : May cause sensitisation by skin contact. May produce an allergic reaction.
- Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.
- Eye contact
- Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not met.
- Ingestion
- Acute toxicity : May cause signs of intoxication and reduced consciousness after exposure to high concentrations. May cause a feeling of sickness, malaise, shortness of breath and lack of breathe. Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: 3 %. ATE: 500 mg/kg.bw.
- Aspiration : Does not contain substances with an aspiration hazard. Not classified - based on available data, the classification criteria are not met.
- Chronic toxicity : Possibility of organ or organ system damage due to prolonged exposure.
- Corrosion/irritation : May cause a feeling of sickness, vomiting and diarrhoea. Not classified - based on available data, the classification criteria are not met.
- Carcinogenicity : Not classified - based on available data, the classification criteria are not met.
- Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.
- Reprotoxicity : Development: Not expected to be reprotoxic. Development: Not classified - Based on available data, the classification criteria are not met. Fertility: not expected to be reprotoxic.

### Toxicological information:

Chemical name	Property		Method	Test animal	
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	NOAEL (development, oral)	750 mg/kg bw/d		Rat	
	Genotoxicity - in vivo	Not genotoxic	OECD 486	Rat	
	NOAEL (inhalation)	30 mg/m <sup>3</sup>	OECD 412	Rat	
	NOAEL (oral)	64,1 mg/kg bw/d	OECD 408	Rat	
	Eye irritation	Slightly irritant	OECD 405	Rabbit	
	Skin irritation	Non-irritant	OECD 404	Rabbit	
	LD50 (dermal)	> 4000 mg/kg bw	OECD 402	Rat	
	LC50 (inhalation)	371 mg/m <sup>3</sup>	OECD 403	Rat	
	Skin sensitisation	Sensitizing.	----	Guinea pig	
	NOEL (carcinogenicity) - estimate	Not carcinogenic	----	Mouse	
	LD50 (oral)	1000 mg/kg bw	OECD 401	Rat	
	Ethane-1,2-diol	LD50 (dermal)	10600 mg/kg bw		
		Mutagenicity	Not mutagenic		
		Genotoxicity - in vitro	Not genotoxic		
Skin irritation		Non-irritant		Rabbit	
Skin sensitisation		Not sensitizing	OECD 406	Guinea pig	
NOEL (inhalation)		71 mg/m <sup>3</sup>			
LD50 (oral)		7712 mg/kg bw	----	Rat	
Eye irritation		Non-irritant		Rabbit	
LD50 (oral) - estimate		500 mg/kg bw			
LC50 (inhalation)		> 2500 mg/m <sup>3</sup>	----	Rat	
LC50 (inhalation) - estimate	> 5000 mg/m <sup>3</sup>				
NOAEL (oral)	150 mg/kg bw/d	OECD 452	Rat		
NOAEL (development, oral)	250 mg/kg bw/d		Rat		



## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

	NOEL (carcinogenicity, oral)	1000 mg/kg bw/d		Rat
--	------------------------------	-----------------	--	-----

Other information : Ethane-1,2-diol There is a marked difference in acute oral toxicity between rodents and man, man being more susceptible than rodents. The estimated fatal dose for man is 100 millilitres (1/2 cup).

## SECTION 12 ECOLOGICAL INFORMATION

### 12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity : Calculated LC50 (fish): 7110 mg/l. Calculated EC50 (waterflea): 228 mg/l. Contains 15 % of components with unknown hazards to the aquatic environment. Not classified - based on available data, the classification criteria are not met.

### 12.2. Persistence and degradability

Persistence – degradability : No specific information known.

### 12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

### 12.4. Mobility in soil

Mobility : Spilled product can penetrate into the ground and get into the surface water and ground water.

### 12.5. Results of PBT and vPvB ass

PBT/vPvB assessment : Does not contain PBT or vPvB substances.

### 12.6. Other adverse effects

Other information : Not applicable.

## SECTION 13 DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Product residues : Do not dispose empty pack with waste produced by households. Containers should be recycled or re-used. Treat product residues and non-empty pack as hazardous waste.

Additional warning : None.

Waste water discharge : Avoid discharge of waste water arising from tank cleaning to the environment.

European waste catalogue : Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

## SECTION 14 TRANSPORT INFORMATION

### 14.1. UN number

UN nr. : None.

### 14.2. UN proper shipping name

Transport name : Not regulated.





## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

#### 14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railway/inland waterways)

Class : This product is not classified according to ADR/RID/ADN.

IMDG (sea)

Class : This product is not classified according to IMDG.

Marine pollutant : No

IATA (air)

Class : This product is not classified according to IATA.

#### 14.6. Special precautions for user

Other information : Country specific variations may apply.

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO) instruments. Packaged liquids are not considered bulk.

## SECTION 15 REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations : Regulation (EC) No 453/2010 (REACH), Regulation (EC) No 1272/2008 (CLP) and other regulations.

#### 15.2. Chemical safety assessment

Chemical safety assessment : Not applicable.

## SECTION 16 OTHER INFORMATION

#### 16.1. Other information

The information in this safety data sheet is compiled in compliance with Regulation (EC) No 453/2010 dated 20 May 2010 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (\*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	: Acute Toxicity Estimate
CLP	: Classification, Labeling & Packaging
CMR	: Carcinogenic, Mutagenic or toxic for Reproduction
EEC	: European Economic Community
IATA	: International Air Transport Association
IBC code	: International Bulk Chemical Code
IMDG	: International Maritime Dangerous Goods Code
LD50/LC50	: Lethal Dose/Concentration for 50% of a population
MAC	: Maximum Allowable Concentration



## Safety data sheet

According to Regulation (EU) No 453/2010

### Bar's Leaks Radiator Stop Leak

---

MARPOL	: International Convention for the Prevention of Pollution From Ships
NO(A)EL	: No Observed (Adverse) Effect Level
OECD	: Organisation for Economic Co-operation and Development
PBT	: Persistent, Bioaccumulative and Toxic
PC	: Chemical product category
PT	: Product type
REACH	: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	: Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	: Sewage Treatment Plant
SU	: Sector of Use
TWA/STEL	: Time-Weighted Average/Short Term Exposure Limit
UN	: United Nations
VOC	: Volatile Organic Compounds
vPvB	: Very Persistent and Very Bioaccumulative

Full text of hazard classes mentioned in section 3:

Acute Tox. 2	: Acute toxicity, Hazard Category 2.
Acute Tox. 4	: Acute toxicity, category 4.
Skin Irrit. 2	: Skin irritation, category 2.
Eye Irrit. 2	: Eye irritation, category 2.
Skin Sens. 1	: Skin sensitization, category 1.
STOT SE 3	: Specific target organ toxicity after single exposure, category 3.
STOT RE 1	: Specific target organ toxicity — repeated exposure, category 1.
STOT RE 2	: Specific target organ toxicity — repeated exposure, category 2.

Full text of H-phrases mentioned in section 3:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

Number format : ", " used as decimal separator.

---

#### History

Date of first issue : 10-11-2015