



Super Friction Proofing®

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

MSDS Version: E06.02

Date of issue: 21/06/2017

Blend Version: 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Super Friction Proofing®

Product code : W66963

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Oil additive

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn's Belgium
Industriepark-West 46
9100 Sint-Niklaas - Belgium
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.com

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45 (NL FR EN DE)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	10 - 25	Not classified
polyhydroxystearic acid	(CAS-No.) 58128-22-6	5 - 10	Skin Irrit. 2, H315
Reaction Mass Of Isomers Of: C7-9-Alkyl 3-(3,5-Di-Tert-Butyl-4-Hydroxyphenyl)Propionate	(CAS-No.) 125643-61-0 (EC-No.) 406-040-9 (EC Index-No.) 607-530-00-7 (REACH-no) 01-2119878226-29 / 01-0000015551-76	1 - 2,5	Aquatic Chronic 4, H413

Full text of H-statements: see section 16

Super Friction Proofing®

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. AFFF foam. ABC-powder.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Explosion hazard : Product is not explosive.

5.3. Advice for firefighters

- Firefighting instructions : Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No open flames. No smoking.

6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable gloves and eye/face protection.
- Emergency procedures : Mark the danger area. Take off contaminated clothing and wash before reuse.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Impound and recover large spill. Contain leaking substance, pump over in suitable containers.
- Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.
- Other information : Caution : this product can cause the floor to be very slippery.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

Super Friction Proofing®

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Presents no particular risk when handled in accordance with good occupational hygiene practice. Meet the legal requirements.
Hygiene measures	: Use good personal hygiene practices. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Does not require any specific or particular technical measures.
Storage conditions	: Meet the legal requirements. Store in a dry place. Store in a closed container.
Storage area	: Meet the legal requirements. Protect from heat and direct sunlight.
Special rules on packaging	: Meet the legal requirements. Labelling according to.

7.3. Specific end use(s)

See product bulletin for detailed information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

EU	IOELV TWA (mg/m ³)	5 mg/m ³
Italy - Portugal - USA	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH		

Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified (64742-54-7)

PNEC (Oral)	
PNEC oral (secondary poisoning)	9,33 mg/kg food

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

PNEC (Oral)	
PNEC oral (secondary poisoning)	9,33 mg/kg food

N-phenylbenzenamine, reaction products with 2,4,4-trimethylpentene (68411-46-1)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,08 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,6 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0,04 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,14 mg/m ³
Long-term - systemic effects, dermal	0,04 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,034 mg/l
PNEC aqua (marine water)	0,003 mg/l
PNEC aqua (intermittent, freshwater)	0,51 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,446 mg/kg dwt
PNEC sediment (marine water)	0,045 mg/kg dwt
PNEC (Soil)	
PNEC soil	2,59 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

Reaction Mass Of Isomers Of: C7-9-Alkyl 3-(3,5-Di-Tert-Butyl-4-Hydroxyphenyl)Propionate (125643-61-0)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	8,6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0,43 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,74 mg/m ³
Long-term - systemic effects, dermal	4,3 mg/kg bodyweight/day
PNEC (Sediment)	

Super Friction Proofing®

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reaction Mass Of Isomers Of: C7-9-Alkyl 3-(3,5-Di-Tert-Butyl-4-Hydroxyphenyl)Propionate (125643-61-0)

PNEC sediment (freshwater)	0,37 mg/kg dwt
PNEC sediment (marine water)	0,037 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,632 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures.

Personal protective equipment

: Gloves. Safety glasses.



Hand protection

: Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.

Other information

: Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Highly viscous material.
Colour	: brown.
Odour	: Oily.
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	: 1,48
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 180 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 877 kg/m ³
Solubility	: insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: 98 mm ² /s
Viscosity, dynamic @40°C	: No data available
Viscosity	: 12,6 mm ² /s @100°C
Viscosity Index	:
	123
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

Super Friction Proofing®

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

9.2. Other information

VOC content	: 0 %
Other properties	: Dimethylsulfoxide (DMSO) <3%.
Additional information	: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

LD50 oral rat	> 5000 mg/kg bodyweight Sprague-Dawley
LD50 dermal rabbit	> 2000 mg/kg bodyweight New Zealand White
LC50 inhalation rat (mg/l)	> 5,53 mg/l/4h Sprague-Dawley

Reaction Mass Of Isomers Of: C7-9-Alkyl 3-(3,5-Di-Tert-Butyl-4-Hydroxyphenyl)Propionate (125643-61-0)

LD50 oral rat	> 2000 mg/kg bodyweight Sprague-Dawley
LD50 dermal rat	> 2000 mg/kg bodyweight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : This product contains hazardous components for the aquatic environment.

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

LC50 fish 1	> 100 mg/l @96h Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	<= 100 mg/l @72h Pseudokirchneriella subcapitata

Reaction Mass Of Isomers Of: C7-9-Alkyl 3-(3,5-Di-Tert-Butyl-4-Hydroxyphenyl)Propionate (125643-61-0)

LC50 fish 1	> 100 mg/l @14d Oncorhynchus mykiss
EC50 Daphnia 1	> 100 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	> 3 mg/l @ 72h Desmodesmus subspicatus
NOEC (acute)	>= 3 mg/l @ 72h Desmodesmus subspicatus

Super Friction Proofing®

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.
European List of Waste (LoW) code : 12 01 12* - spent waxes and fats
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

Super Friction Proofing®

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

Water hazard class (WGK) : 1 - low hazard to waters

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 4

Hazardous to the aquatic environment — Chronic Hazard, Category 4

Skin Irrit. 2

Skin corrosion/irritation, Category 2

H315

Causes skin irritation

H413

May cause long lasting harmful effects to aquatic life

EUH210

Safety data sheet available on request

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product