



Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

MSDS Version: E04.00

Date of issue: 20/02/2015

Blend Version: 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Fuel System Cleaner
Product code : W61351

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Petrol additive.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn's Belgium
Industriepark-West 46
9100 Sint-Niklaas - Belgium
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.be

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336
STOT RE 1	H372
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11
Xn; R65
Xn; R48/20
R66
R67
R52/53

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

Hazardous ingredients : hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects

EUH phrases : EUH066 - Repeated exposure may cause skin dryness or cracking
Precautionary statements (CLP) : P102 - Keep out of reach of children
P405 - Store locked up
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe vapours
P280 - Wear eye protection
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor
P331 - Do NOT induce vomiting
P273 - Avoid release to the environment

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% w	Classification according to Directive 67/548/EEC
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC no) 919-164-8 (REACH-no) 01-2119473977-17	50 - 75	Xn; R48/20 Xn; R65 R66
Propan-2-ol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0 (REACH-no) 01-2119457558-25	10 - 25	F; R11 Xi; R36 R67
4-methylpentan-2-ol	(CAS No) 108-11-2 (EC no) 203-551-7 (EC index no) 603-008-00-8 (REACH-no) 01-2119473979-13	2,5 - 5	R10 Xi; R36/37/38
1-Propene, 2-methyl-, homopolymer, hydroformylation products, reaction products with ammonia	(CAS No) 337367-30-3	2,5 - 5	Xi; R38 R52/53
Polyether	(CAS No) 173140-85-7 (EC no) polymer	2,5 - 5	Xi; R38
Paraffins, normal C5-20	(CAS No) 64771-72-8 (EC no) 265-233-4 (REACH-no) 01-2119475608-26	1 - 2,5	Xn; R65 R66
Solvent naphtha (petroleum), heavy aromatic	(CAS No) 64742-94-5 (EC no) 265-198-5 (EC index no) 649-424-00-3	1 - 2,5	Xn; R65 N; R51/53 R66 R67
Naphthalene	(CAS No) 91-20-3 (EC no) 202-049-5 (EC index no) 601-052-00-2 (REACH-no) 01-2119561346-37	0,1 - 1	Carc.Cat.3; R40 Xn; R22 N; R50/53

Name	Product identifier	Specific concentration limits
4-methylpentan-2-ol	(CAS No) 108-11-2 (EC no) 203-551-7 (EC index no) 603-008-00-8 (REACH-no) 01-2119473979-13	(C >= 25) Xi;R37

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC no) 919-164-8 (REACH-no) 01-2119473977-17	50 - 75	STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Propan-2-ol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0 (REACH-no) 01-2119457558-25	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
4-methylpentan-2-ol	(CAS No) 108-11-2 (EC no) 203-551-7 (EC index no) 603-008-00-8 (REACH-no) 01-2119473979-13	2,5 - 5	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335
1-Propene, 2-methyl-, homopolymer, hydroformylation products, reaction products with ammonia	(CAS No) 337367-30-3	2,5 - 5	Skin Irrit. 2, H315 Aquatic Chronic 3, H412
Polyether	(CAS No) 173140-85-7 (EC no) polymer	2,5 - 5	Skin Irrit. 2, H315
Paraffins, normal C5-20	(CAS No) 64771-72-8 (EC no) 265-233-4 (REACH-no) 01-2119475608-26	1 - 2,5	Asp. Tox. 1, H304
Solvent naphtha (petroleum), heavy aromatic	(CAS No) 64742-94-5 (EC no) 265-198-5 (EC index no) 649-424-00-3	1 - 2,5	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Naphthalene	(CAS No) 91-20-3 (EC no) 202-049-5 (EC index no) 601-052-00-2 (REACH-no) 01-2119561346-37	0,1 - 1	Carc. 2, H351 Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	Specific concentration limits
4-methylpentan-2-ol	(CAS No) 108-11-2 (EC no) 203-551-7 (EC index no) 603-008-00-8 (REACH-no) 01-2119473979-13	(C >= 25) STOT SE 3, H335

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Victim conscious with laboured breathing: half-seated. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: skin corrosion/irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Abdominal pain. May be fatal if swallowed and enters airways. Risk of aspiration pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Alcohol resistant foam. ABC-powder.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour. This material can accumulate static charge by flow or agitation and can be ignited by static discharge.
Explosion hazard	: No direct explosion hazard.

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

5.3. Advice for firefighters

- Firefighting instructions : Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Face-shield. Gloves. protective clothing.
Emergency procedures : Mark the danger area. Seal off low-lying areas. Large spills/in enclosed spaces: compressed air apparatus. Wash contaminated clothes.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain leaking substance, pump over in suitable containers.
Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

- No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : meet the legal requirements. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin. Presents no particular risk when handled in accordance with good occupational hygiene practice.
Hygiene measures : Observe normal hygiene standards. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Meet the legal requirements. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place.
Storage temperature : < 45 °C
Storage area : Meet the legal requirements. Keep container tightly closed in a cool, well-ventilated place. Ventilation along the floor.
Special rules on packaging : Keep only in original container. correctly labelled.

7.3. Specific end use(s)

- No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Italy - Portugal - USA ACGIH TWA (ppm) 100 ppm
ACGIH

Propan-2-ol (67-63-0)

Belgium Limit value (mg/m³) 500 mg/m³
Belgium Limit value (ppm) 200 ppm
Belgium Short time value (mg/m³) 1000 mg/m³
Belgium Short time value (ppm) 400 ppm

4-methylpentan-2-ol (108-11-2)

Belgium Limit value (mg/m³) 106 mg/m³
Belgium Limit value (ppm) 25 ppm
Belgium Short time value (mg/m³) 169 mg/m³

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

4-methylpentan-2-ol (108-11-2)

Belgium	Short time value (ppm)	40 ppm
Belgium	Remark (BE)	D
France	VME (mg/m ³)	100 mg/m ³
France	VME (ppm)	25 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	85 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	25 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	40 ppm
United Kingdom	WEL TWA (mg/m ³)	106 mg/m ³
United Kingdom	WEL TWA (ppm)	25 ppm
United Kingdom	WEL STEL (mg/m ³)	170 mg/m ³
United Kingdom	WEL STEL (ppm)	40 ppm

Naphthalene (91-20-3)

EU	IOELV TWA (mg/m ³)	50 mg/m ³
EU	IOELV TWA (ppm)	10 ppm
Belgium	Limit value (mg/m ³)	53 mg/m ³
Belgium	Limit value (ppm)	10 ppm
Belgium	Short time value (mg/m ³)	80 mg/m ³
Belgium	Short time value (ppm)	15 ppm
Belgium	Remark (BE)	D

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures.

Personal protective equipment

: Gloves. Safety glasses.



Hand protection

: Neoprene, nitrile. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.

Other information

: Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Colourless.
Odour	: Alcohol.
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	: 1,435
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 75 °C
Flash point	: 17 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 805 kg/m ³
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: 1,52 mm ² /s
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 93,4 %
Additional information	: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful: may cause lung damage if swallowed

Naphthalene (91-20-3)

ATE CLP (oral)	500,000 mg/kg bodyweight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Causes damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long lasting harmful effects to aquatic life.

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Ecology - water : Harmful to aquatic life with long lasting effects.

Naphthalene (91-20-3)

LC50 fish 1 : 6,08 mg/l 96h

12.2. Persistence and degradability

Propan-2-ol (67-63-0)

Persistence and degradability : Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.

4-methylpentan-2-ol (108-11-2)

Persistence and degradability : Readily biodegradable in water. Biodegradable in the soil.

12.3. Bioaccumulative potential

Propan-2-ol (67-63-0)

Bioaccumulative potential : Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Remove to an authorized waste treatment plant.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1993

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S.

Transport document description (ADR) : UN 1993 FLAMMABLE LIQUID, N.O.S. (Isopropanol), 3, II, (D/E)

14.3. Transport hazard class(es)

Class (ADR) : 3

Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : II

14.5. Environmental hazards

Other information : No supplementary information available.


14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 33

Classification code (ADR) : F1

Orange plates :



Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Special provisions (ADR) : 274, 601, 640D
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E2
EAC code : •3YE

14.6.2. Transport by sea

EmS-No. (1) : F-E, S-E

14.6.3. Air transport

Instruction "cargo" (ICAO) : 364
Instruction "passenger" (ICAO) : 353
Instruction "passenger" - Limited quantities (ICAO) : Y341

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions
Fuel System Cleaner is not on the REACH Candidate List
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances
VOC content : 93,4 %

15.1.2. National regulations

Water hazard class (WGK) : 2 - hazard to waters

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 453/2010

H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
R10	Flammable
R11	Highly flammable
R22	Harmful if swallowed
R36	Irritating to eyes
R36/37/38	Irritating to eyes, respiratory system and skin
R38	Irritating to skin
R40	Limited evidence of a carcinogenic effect
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product