



Red Gasket Maker (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

MSDS Version: E06.00

Date of issue: 01/12/2017

Blend Version: 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Red Gasket Maker (Aerosol)
Product code : W10807

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Adhesives, sealants
Function or use category : Aerosol propellants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn's Belgium
Industriepark-West 46
9100 Sint-Niklaas - Belgium
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.com

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45 (NL FR EN DE)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 3 H229

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : Warning
Hazard statements (CLP) : H229 - Pressurised container: May burst if heated.
Precautionary statements (CLP) : P102 - Keep out of reach of children.
P280 - Wear protective gloves, eye protection, Protective clothing.
P264 - Wash hands thoroughly after handling.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 - Do not pierce or burn, even after use.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

Other hazards not contributing to the classification : When processed: release of corrosive gases/vapours (acetic acid vapours).

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
trans-1,3,3,3-tetrafluoroprop-1-ene (HFO-1234ze)	(CAS-No.) 29118-24-9	1 - 5	Press. Gas (Liq.), H280

Red Gasket Maker (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	(EC-No.) 471-480-0 (REACH-no) 01-0000019758-54		
methylsilanetriyl triacetate	(CAS-No.) 4253-34-3 (EC-No.) 224-221-9 (REACH-no) 01-2119962266-32	1 - 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314
propyltriacetoxysilane	(CAS-No.) 17865-07-5 (EC-No.) 241-816-9 (REACH-no) 01-2119966899-07	1 - 5	Skin Corr. 1B, H314

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth out with water. Call a POISON CENTER/doctor if you feel unwell. As it is a spray can packaging it is most unlikely that large quantities will be swallowed.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause eye, skin and respiratory system irritation.
- Symptoms/effects after eye contact : Vapours may cause delayed painful eye irritation and tearing.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : All extinguishing agents can be used.
- Unsuitable extinguishing media : None to our knowledge. If there is a fire close by, use suitable extinguishing agents.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not classified as flammable aerosol.
- Explosion hazard : Product is not explosive. Pressurised container: May burst if heated.

5.3. Advice for firefighters

- Firefighting instructions : Fight fire from safe distance and protected location. Cool closed containers exposed to fire with water spray.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : In case of fire, corrosive and harmful gases come free.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable gloves and eye/face protection. protective clothing.
- Emergency procedures : Mark the danger area. Keep upwind. Avoid contact with skin, eyes and clothing. In confined space use self-contained breathing apparatus. Take off contaminated clothing.

6.1.2. For emergency responders

- Emergency procedures : Ventilate area.

Red Gasket Maker (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spillage. Shovel or sweep up and put in a closed container for disposal. Dispose in a safe manner in accordance with local/national regulations. Clean preferably with a detergent - Avoid the use of solvents.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use. When handling product, avoid contact with skin and eyes. Do not pierce or burn, even after use.

Precautions for safe handling : Presents no particular risk when handled in accordance with good occupational hygiene practice. Provide good ventilation in process area to prevent formation of vapour. Meet the legal requirements.

Hygiene measures : Use good personal hygiene practices. Wash contaminated clothing before reuse. IF ON SKIN: Gently wash with plenty of soap and water.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep out of frost.

Storage conditions : Store in a dry place.

Storage temperature : 5 - 25 °C

Heat and ignition sources : Keep away from heat.

Storage area : Meet the legal requirements. Protect from heat and direct sunlight. Store in a well-ventilated place.

Special rules on packaging : Meet the legal requirements. Labelling according to.

Packaging materials : Aerosol.

7.3. Specific end use(s)

Adhesives, sealants. See product bulletin for detailed information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

trans-1,3,3,3-tetrafluoroprop-1-ene (HFO-1234ze) (29118-24-9)

DNEL/DMEL (Workers)

Long-term - systemic effects, inhalation 3902 mg/m³

DNEL/DMEL (General population)

Long-term - systemic effects, inhalation 830 mg/m³

PNEC (Water)

PNEC aqua (freshwater) 0,1 mg/l

methylsilanetriyl triacetate (4253-34-3)

DNEL/DMEL (Workers)

Acute - local effects, inhalation 31 mg/m³

Long-term - local effects, inhalation 31 mg/m³

DNEL/DMEL (General population)

Acute - local effects, inhalation 5,1 mg/m³

Long-term - local effects, inhalation 5,1 mg/m³

PNEC (Water)

PNEC aqua (freshwater) 1 mg/l

PNEC aqua (marine water) 0,1 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 3,4 mg/kg dwt

PNEC sediment (marine water) 0,34 mg/kg dwt

PNEC (Soil)

PNEC soil 0,145 mg/kg dwt

PNEC (STP)

Red Gasket Maker (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

methylsilanetriyl triacetate (4253-34-3)

PNEC sewage treatment plant 6,9 mg/l

propyltriacetoxysilane (17865-07-5)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal 12,11 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 85,39 mg/m³

DNEL/DMEL (General population)

Long-term - systemic effects, oral 6,05 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 21,06 mg/m³

Long-term - systemic effects, dermal 6,05 mg/kg bodyweight/day

PNEC (Water)

PNEC aqua (freshwater) 0,024 mg/l

PNEC aqua (marine water) 0,002 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 0,015 mg/kg dwt

PNEC sediment (marine water) 0,001 mg/kg dwt

PNEC (Soil)

PNEC soil 0,003 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 10,55 mg/l

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide good ventilation in process area to prevent formation of vapour. Does not require any specific or particular technical measures.

Personal protective equipment

: Gloves. Safety glasses. Protective clothing.



Hand protection

: Polyvinylchloride (PVC). Nitrile rubber. Neoprene. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.

Eye protection

: Safety glasses with side shields.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

: Use appropriate container to avoid environmental contamination.

Other information

: Breakthrough time : >30'. Thickness of the glove material >0.1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol. Paste.
Colour	: red.
Odour	: acetic acid.
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	:
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 61 °C
Auto-ignition temperature	: No data available

Red Gasket Maker (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1,22
Solubility	: insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: No data available
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

Additional information : Physical and chemical properties of the active product without gas. The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Pressurized container. On heating there is a risk of bursting due to internal pressure build-up.

10.4. Conditions to avoid

Heat. Moisture. Polymerizes on exposure to water (moisture). Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. On burning: release of harmful/irritant gases/vapours. Burning produces stinking and toxic fumes. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

trans-1,3,3,3-tetrafluoroprop-1-ene (HFO-1234ze) (29118-24-9)

LC50 inhalation rat (ppm) > 207000 ppm/4h Sprague-Dawley

methylsilanetriyl triacetate (4253-34-3)

LD50 oral rat 1550 - 1660 mg/kg bodyweight Sprague-Dawley

ATE CLP (oral) 1550 mg/kg bodyweight

Skin corrosion/irritation : Not classified.

Based on available data, the classification criteria are not met

Serious eye damage/irritation : Not classified

Based on available data, the classification criteria are not met

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Red Gasket Maker (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

trans-1,3,3,3-tetrafluoroprop-1-ene (HFO-1234ze) (29118-24-9)

LC50 fish 1	> 117 mg/l @96h Cyprinus carpio
EC50 Daphnia 1	> 160 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	> 170 mg/l @72h Pseudokirchneriella subcapitata

methylsilanetriyl triacetate (4253-34-3)

LC50 fish 1	> 500 mg/l @96h Brachydanio rerio
EC50 Daphnia 1	> 500 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	> 500 mg/l @72h Pseudokirchneriella subcapitata
NOEC (acute)	72h 500 mg/l Pseudokirchneriella subcapitata

propyltriacetoxysilane (17865-07-5)

LC50 fish 1	96h 10000 mg/l Pimephales promelas
EC50 Daphnia 1	48h 65 mg/l Daphnia magna
EC50 other aquatic organisms 1	72h 24,41 mg/l growth rate - Pseudokirchneriella subcapitata
LOEC (acute)	72h 32 mg/l Pseudokirchneriella subcapitata
NOEC (acute)	72h 18 mg/l Pseudokirchneriella subcapitata

12.2. Persistence and degradability

Red Gasket Maker (Aerosol)

Persistence and degradability	No data available.
-------------------------------	--------------------

12.3. Bioaccumulative potential

Red Gasket Maker (Aerosol)

Bioaccumulative potential	No bioaccumulation.
---------------------------	---------------------

trans-1,3,3,3-tetrafluoroprop-1-ene (HFO-1234ze) (29118-24-9)

Log Pow	1,6
---------	-----

methylsilanetriyl triacetate (4253-34-3)

Bioaccumulative potential	Slightly bioaccumulative.
---------------------------	---------------------------

12.4. Mobility in soil

Red Gasket Maker (Aerosol)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Remove to an authorized waste treatment plant.
European List of Waste (LoW) code	: 18 01 06* - chemicals consisting of or containing dangerous substances 16 05 05 - gases in pressure containers other than those mentioned in 16 05 04

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1950
--------------	--------

Red Gasket Maker (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Transport document description (ADR) : UN 1950 AEROSOLS, 2.2, (E)

14.3. Transport hazard class(es)

Class (ADR) : 2
Danger labels (ADR) : 2.2



14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Classification code (ADR) : 5A
Special provisions (ADR) : 190, 327, 344, 625
Transport category (ADR) : 3
Tunnel restriction code (ADR) : E
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0

14.6.2. Transport by sea

EmS-No. (1) : F-D, S-U

14.6.3. Air transport

Instruction "cargo" (ICAO) : 203
Instruction "passenger" (ICAO) : 203/Y203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

Water hazard class (WGK) : 1 - low hazard to waters

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). according to Regulation (EU) 2015/830.

Red Gasket Maker (Aerosol)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)

Aerosol 3

Press. Gas (Liq.)

Skin Corr. 1B

Skin Corr. 1C

H229

H280

H302

H314

Acute toxicity (oral), Category 4

Aerosol, Category 3

Gases under pressure : Liquefied gas

Skin corrosion/irritation, Category 1B

Skin corrosion/irritation, Category 1C

Pressurised container: May burst if heated.

Contains gas under pressure; may explode if heated.

Harmful if swallowed.

Causes severe skin burns and eye damage.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product