



Prestone



## SAFETY DATA SHEET PRIMER LACQUER GREY

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** PRIMER LACQUER GREY  
**Product number** RF0170C

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** A Holts Car Care Product  
Holt Lloyd International Ltd  
Barton Dock Road  
Stretford  
Manchester  
M32 0YQ - England, UK  
+44 (0) 161 866 4800  
FAX +44 (0) 161 866 4854  
www.holtsauto.com

**Contact person** Contact Email address: info@holtsauto.com

#### 1.4. Emergency telephone number

**Emergency telephone** UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167

**National emergency telephone number** <http://echa.europa.eu/en/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks>

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture


##### Classification

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336  
**Environmental hazards** Aquatic Chronic 3 - H412

**Classification (67/548/EEC or 1999/45/EC)** Xi;R36. F+;R12. N;R51/53. R66,R67.

#### 2.2. Label elements

##### Pictogram



**Signal word** Danger

## PRIMER LACQUER GREY

<b>Hazard statements</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P501 Dispose of contents/container in accordance with local regulations.
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	ACETONE, BUTYL ACETATE -norm, BUTANONE, BUTANOL-norm

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>DIMETHYL ETHER</b>	<b>30-60%</b>
CAS number: 115-10-6	EC number: 204-065-8
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Gas 1 - H220	F+;R12
Press. Gas	
<b>ACETONE</b>	<b>10-30%</b>
CAS number: 67-64-1	EC number: 200-662-2
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

## PRIMER LACQUER GREY

<b>ISOBUTANE</b>		<b>5-10%</b>
CAS number: 75-28-5		EC number: 200-857-2
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Gas 1 - H220	F+;R12	
Press. Gas		
<b>BUTYL ACETATE -norm</b>		<b>5-10%</b>
CAS number: 123-86-4		EC number: 204-658-1
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	R10 R66 R67	
STOT SE 3 - H336		
<b>BUTANE</b>		<b>5-10%</b>
CAS number: 106-97-8		EC number: 203-448-7
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Gas 1 - H220	F+;R12	
Press. Gas		
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>		<b>1-5%</b>
CAS number: 108-65-6		EC number: 203-603-9
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	R10 Xi;R36	
<b>BUTANONE</b>		<b>1-5%</b>
CAS number: 78-93-3		EC number: 201-159-0
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67	
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
<b>BUTANOL-norm</b>		<b>1-5%</b>
CAS number: 71-36-3		EC number: 200-751-6
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	R10 Xn;R22 Xi;R37/38,R41 R67	
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
Acute Tox. 4 - H302		
STOT SE 3 - H335, H336		

## PRIMER LACQUER GREY

<b>TRIZINC BIS(ORTHOPHOSPHATE)</b>		<b>1-5%</b>
CAS number: 7779-90-0	EC number: 231-944-3	
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Aquatic Acute 1 - H400	N;R50/53	
Aquatic Chronic 1 - H410		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting.
<b>Skin contact</b>	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Use fire-extinguishing media suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Move containers from fire area if it can be done without risk.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

#### 6.4. Reference to other sections

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

## PRIMER LACQUER GREY

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage class** Flammable compressed gas storage.

### 7.3. Specific end use(s)

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### **DIMETHYL ETHER**

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m<sup>3</sup>

##### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **ISOBUTANE**

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

##### **BUTYL ACETATE -norm**

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

##### **BUTANE**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

##### **2-METHOXY-1-METHYLETHYL ACETATE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m<sup>3</sup>(Sk)

##### **BUTANONE**

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m<sup>3</sup>(Sk)

##### **BUTANOL-norm**

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m<sup>3</sup>(Sk)

WEL = Workplace Exposure Limit

### 8.2. Exposure controls

#### **Protective equipment**



#### **Eye/face protection**

The following protection should be worn: Chemical splash goggles.

#### **Hand protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. EN374 It is recommended that gloves are made of the following material: Rubber (natural, latex).

## PRIMER LACQUER GREY

<b>Other skin and body protection</b>	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
<b>Hygiene measures</b>	Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.
<b>Respiratory protection</b>	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Grey.
<b>Flash point</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 2.6% Upper flammable/explosive limit: 18.6%
<b>Relative density</b>	~0.7945 @ °C
<b>Auto-ignition temperature</b>	235°C

#### 9.2. Other information

<b>Volatility</b>	88.7%
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 704.6 g/litre.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

#### 10.2. Chemical stability

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.
----------------------------	---

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Thermal decomposition or combustion products may include the following substances: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO).
---	---

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - oral

<b>ATE oral (mg/kg)</b>	20,000.0
-------------------------	----------

<b>Inhalation</b>	Vapours may cause headache, fatigue, dizziness and nausea. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache.
-------------------	---

<b>Ingestion</b>	No harmful effects expected from quantities likely to be ingested by accident.
------------------	--

## PRIMER LACQUER GREY

<b>Skin contact</b>	Prolonged and frequent contact may cause redness and irritation.
<b>Eye contact</b>	Irritating to eyes. Repeated exposure may cause chronic eye irritation.
<b>Route of entry</b>	Inhalation Skin and/or eye contact

### SECTION 12: Ecological Information

<b>Ecotoxicity</b>	Not regarded as dangerous for the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
--------------------	---

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>Disposal methods</b>	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion.
-------------------------	--

<b>Waste class</b>	WGK: 1 (Germany)
--------------------	------------------

### SECTION 14: Transport information

#### 14.1. UN number

<b>UN No. (ADR/RID)</b>	1950
<b>UN No. (IMDG)</b>	1950
<b>UN No. (ICAO)</b>	1950
<b>UN No. (ADN)</b>	1950

#### 14.2. UN proper shipping name

<b>Proper shipping name (ADR/RID)</b>	AEROSOLS
<b>Proper shipping name (IMDG)</b>	AEROSOLS
<b>Proper shipping name (ICAO)</b>	AEROSOLS
<b>Proper shipping name (ADN)</b>	AEROSOLS

#### 14.3. Transport hazard class(es)

<b>ADR/RID class</b>	2.1
<b>ADR/RID classification code</b>	5F
<b>ADR/RID label</b>	2.1
<b>IMDG class</b>	2.1
<b>ICAO class/division</b>	2.1

## PRIMER LACQUER GREY

ADN class 2.1

### Transport labels



### 14.4. Packing group

ADR/RID packing group None  
 IMDG packing group None  
 ADN packing group None  
 ICAO packing group None

### 14.5. Environmental hazards

#### Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS F-D, S-U  
 ADR transport category 2  
 Tunnel restriction code (D)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
 VOC Directive - 2004/42/EC  
 Aerosol Dispensers Directive 2008/47/EC (2008/47/EC)  
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Water hazard classification** WGK 2

### 15.2. Chemical safety assessment

## SECTION 16: Other information

Revision date 28/09/2015  
 Revision 1  
 Supersedes date 13/08/2013  
 SDS number 14351



## PRIMER LACQUER GREY

### Risk phrases in full

R10 Flammable.  
R11 Highly flammable.  
R12 Extremely flammable.  
R22 Harmful if swallowed.  
R36 Irritating to eyes.  
R37/38 Irritating to respiratory system and skin.  
R41 Risk of serious damage to eyes.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

### Hazard statements in full

H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: may burst if heated  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.