



Prestone



SAFETY DATA SHEET RALLYE BLACK PAINT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	RALLYE BLACK PAINT
Product number	RF0172C
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Paint.
-----------------	--------

1.3. Details of the supplier of the safety data sheet

Supplier	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com
Contact person	Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167
---------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards	Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36. F+;R12. R66,R67.

2.2. Label elements

Pictogram



Signal word Danger

RALLYE BLACK PAINT

Hazard statements	H336 May cause drowsiness or dizziness. H319 Causes serious eye irritation. H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P501 Dispose of contents/container in accordance with local regulations.

Contains ACETONE, BUTYL ACETATE -norm, BUTANOL-norm, BUTANONE

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIMETHYL ETHER	30-60%
CAS number: 115-10-6	EC number: 204-065-8
Classification Flam. Gas 1 - H220 Press. Gas	Classification (67/548/EEC or 1999/45/EC) F+;R12
ACETONE	10-30%
CAS number: 67-64-1	EC number: 200-662-2
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67
BUTANE	5-10%
CAS number: 106-97-8	EC number: 203-448-7
Classification Flam. Gas 1 - H220 Press. Gas	Classification (67/548/EEC or 1999/45/EC) F+;R12

RALLYE BLACK PAINT

BUTYL ACETATE -norm		5-10%
CAS number: 123-86-4		EC number: 204-658-1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 R66 R67	
STOT SE 3 - H336		
2-METHOXY-1-METHYLETHYL ACETATE		5-10%
CAS number: 108-65-6		EC number: 203-603-9
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xi;R36	
ISOBUTANE		5-10%
CAS number: 75-28-5		EC number: 200-857-2
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Gas 1 - H220	F+;R12	
Press. Gas		
BUTANONE		1-5%
CAS number: 78-93-3		EC number: 201-159-0
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67	
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
BUTANOL-norm		1-5%
CAS number: 71-36-3		EC number: 200-751-6
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R22 Xi;R37/38,R41 R67	
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
Acute Tox. 4 - H302		
STOT SE 3 - H335, H336		
ALUMINIUM POWDER (PYROPHORIC)		1-5%
CAS number: 7429-90-5		EC number: 231-072-3
Classification	Classification (67/548/EEC or 1999/45/EC)	
Pyr. Sol. 1 - H250	F;R15,R17	
Water-react. 2 - H261		

RALLYE BLACK PAINT

XYLENE	1-5%
CAS number: 1330-20-7	EC number: 215-535-7
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38
Skin Irrit. 2 - H315	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting.
Skin contact	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

RALLYE BLACK PAINT

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m³(Sk)

BUTANOL-norm

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m³(Sk)

ALUMINIUM POWDER (PYROPHORIC)

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



RALLYE BLACK PAINT

Eye/face protection	The following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. EN374 It is recommended that gloves are made of the following material: Rubber (natural, latex).
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Black.
Flash point	Not applicable.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.6% Upper flammable/explosive limit: 18.6%
Relative density	~0.748 @ °C
Auto-ignition temperature	235°C

9.2. Other information

Volatility	91.9%
Volatile organic compound	This product contains a maximum VOC content of 687.5 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.
----------------------------	---

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon dioxide (CO ₂). Carbon monoxide (CO).
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)	20,000.0
-------------------------	----------

Acute toxicity - dermal

ATE dermal (mg/kg)	110,000.0
---------------------------	-----------

RALLYE BLACK PAINT

Acute toxicity - inhalation

ATE inhalation (gases ppm) 450,000.0

ATE inhalation (vapours mg/l) 1,100.0

ATE inhalation (dusts/mists mg/l) 150.0

Inhalation Vapours may cause headache, fatigue, dizziness and nausea. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact Irritating to eyes. Repeated exposure may cause chronic eye irritation.

Route of entry Inhalation Skin and/or eye contact

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

RALLYE BLACK PAINT

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78
and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	EH40/2005 Workplace exposure limits.
EU legislation	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.

RALLYE BLACK PAINT

Restrictions (Title VIII Regulation 1907/2006) No specific restrictions on use are known for this product.

Water hazard classification WGK 1

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 24/08/2015

Revision 1

Supersedes date 13/08/2013

SDS number 14294

Risk phrases in full

- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R15 Contact with water liberates extremely flammable gases.
- R17 Spontaneously flammable in air.
- R20/21 Harmful by inhalation and in contact with skin.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R37/38 Irritating to respiratory system and skin.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: may burst if heated
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.