

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2016

Version: 1

Revision: 01.06.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** SONAX PROFILINE EX 04/06

**Article number:** 02420000, 02421410, 02423000, 02425000, 02429050, 02429410-050.01

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category** PC31 Polishes and wax blends

**Application of the substance / the mixture** Car care product

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

##### Further information obtainable from:

Product safety

E-mail: [erp@sonax.de](mailto:erp@sonax.de)

Phone: + 49 (0) 8431 53 217

#### 1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

The product is not classified according to the CLP regulation.

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008** Void

**Hazard pictograms** Void

**Signal word** Void

**Hazard statements** Void

**Precautionary statements** P102 Keep out of reach of children.

#### 2.3 Other hazards

##### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Description:** Emulsion of solvents, abrasives and additives

##### Dangerous components:

EC No 920-114-2 Reg.nr.: 01-2119459347-30-xxxx	Hydrocarbons, C14-C19, isoalkanes, cyclics, < 2% aromatics ⚠ Asp. Tox. 1, H304	15 - <20%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-Methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	1 - <3%

##### Additional information:

Any entry in the EC-column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 15 for additional CAS number information for the substance.

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**General information:** No special measures required.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.10.2016

Version: 1

Revision: 01.06.2016

**Trade name: SONAX PROFILINE EX 04/06**

(Contd. of page 1)

**After inhalation:** Supply fresh air.**After skin contact:**

Wash the areas of skin affected with water and a mild detergent.

Generally the product does not irritate the skin.

**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters****Protective equipment:** The normal measures for firefighting are to be taken.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures** Not required.**6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Pick up mechanically.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** No special precautions are necessary if used correctly.**Information about fire - and explosion protection:** No special measures required.**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.**Information about storage in one common storage facility:** Store away from foodstuffs.**Further information about storage conditions:**

Store receptacle in a well ventilated area.

Protect from frost.

Recommended storage temperature: 20 °C.

**7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.10.2016

Version: 1

Revision: 01.06.2016

Trade name: SONAX PROFILINE EX 04/06

(Contd. of page 2)

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

**Ingredients with limit values that require monitoring at the workplace:**

**CAS: 107-98-2 1-Methoxy-2-propanol**

WEL (Great Britain)	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm Sk
IOELV (EU)	Short-term value: 568 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm Skin

#### DNELs

**CAS: 107-98-2 1-Methoxy-2-propanol**

Oral	DNEL	3.3 mg/kg (consumer) (long-term / systemic effects)
Dermal	DNEL	18.1 mg/kg (consumer) (long-term / systemic effects) 50.6 mg/kg (worker) (long-term / systemic effects)
Inhalative	DNEL	43.9 mg/m <sup>3</sup> (consumer) (long-term / systemic effects) 553.5 mg/m <sup>3</sup> (worker) (short-term / local effects) 369 mg/m <sup>3</sup> (worker) (long-term / systemic effects)

#### PNECs

**CAS: 107-98-2 1-Methoxy-2-propanol**

PNEC	100 mg/l (STP) 2.47 mg/kg (gro) 41.6 mg/kg (sediment (fresh water)) 4.17 mg/kg (sediment (sea water)) 100 mg/l (water (intermittent release)) 10 mg/l (water (fresh water)) 1 mg/l (water (sea water))
------	--

**Additional information:** The lists valid during the making were used as basis.

#### 8.2 Exposure controls

##### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

##### Personal protective equipment:

##### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

##### Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

**Protection of hands:** Not required in normal cases

**Eye protection:** Not required in normal cases

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### General Information

##### Appearance:

Form:	Pasty
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.10.2016

Version: 1

Revision: 01.06.2016

Trade name: SONAX PROFILINE EX 04/06

(Contd. of page 3)

<b>pH-value:</b>	Not applicable.
<b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	100 - 335 °C
<b>Flash point:</b>	Not applicable.
<b>Flammability (solid, gaseous):</b>	Not applicable.
<b>Ignition temperature:</b>	
<b>Decomposition temperature:</b>	Not determined.
<b>Self-igniting:</b>	Product is not selfigniting.
<b>Danger of explosion:</b>	Product does not present an explosion hazard.
<b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density at 20 °C:</b>	0.98 - 0.99 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Solubility in / Miscibility with water:</b>	Partly miscible.
<b>Partition coefficient (n-octanol/water):</b>	Not determined.
<b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 40 °C:</b>	>20.5 mm <sup>2</sup> /s
<b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No dangerous reactions known.

**10.2 Chemical stability** Stable under normal conditions.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.

**10.4 Conditions to avoid** See Section 7 for information on safe handling.

**10.5 Incompatible materials:** strong oxidizing agents

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

**11.1 Information on toxicological effects** There are no toxicological findings on this mixture.

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

**Hydrocarbons, C14-C19, isoalkanes, cyclics, < 2% aromatics**

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4h	>5266 mg/l (rat) (Aerosol (OECD 403))

**CAS: 107-98-2 1-Methoxy-2-propanol**

Oral	LD50	4016 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC0 / 6h	>7000 ppm (rat)

(Contd. on page 5)

-GB-

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.10.2016

Version: 1

Revision: 01.06.2016

Trade name: SONAX PROFILINE EX 04/06

(Contd. of page 4)

**Primary irritant effect:****Skin corrosion/irritation**

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

**Serious eye damage/irritation**

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

**Respiratory or skin sensitisation**

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard**Viscosity: > 20,5mm<sup>2</sup>/s (40 °C)

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

**SECTION 12: Ecological information****12.1 Toxicity** There are no ecotoxicological data available on this mixture.**Aquatic toxicity:****Hydrocarbons, C14-C19, isoalkanes, cyclics, < 2% aromatics**

ELO 48 h	1000 mg/l (Daphnia magna)
ErLO 72h	1000 mg/l (Pseudokirchneriella subcapitata)
LL0 96h	87556 mg/l (Oncorhynchus mykiss)
NOELR 21d	5 mg/l (Daphnia magna)
NOELR 72 h	1000 mg/l (Pseudokirchneriella subcapitata)

**CAS: 107-98-2 1-Methoxy-2-propanol**

EC50	>1000 mg/l (Pseudokirchneriella subcapitata) (7d)
EC50/3h	>1000 mg/l (activated sludge) (OECD 209)
LC 50 / 96 h	>6800 mg/l (Leuciscus idus) (DIN38412)
LC50 / 48h	23300 mg/l (Daphnia magna)

**12.2 Persistence and degradability****Hydrocarbons, C14-C19, isoalkanes, cyclics, < 2% aromatics**

Biodegradation | 17.7 % (28d)

**CAS: 107-98-2 1-Methoxy-2-propanol**

Biodegradation | 90 - 100 % (OECD 301E)

**12.3 Bioaccumulative potential****CAS: 107-98-2 1-Methoxy-2-propanol**

log Kow | -0.43 log Kow (25 °C)

**12.4 Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** The product may not be released into the environment without control.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation** Waste must be disposed of while observing the local, official regulations.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.10.2016

Version: 1

Revision: 01.06.2016

Trade name: SONAX PROFILINE EX 04/06

(Contd. of page 5)

**European waste catalogue**

- 1) Disposal / product  
2) Disposal / contaminated packaging

20 01 13*	solvents
15 01 02	plastic packaging
15 01 04	metallic packaging (article 02429050)

**SECTION 14: Transport information**

**14.1 UN-Number**  
ADR, IMDG, IATA                      Void

**14.2 UN proper shipping name**  
ADR, IMDG, IATA                      Void

**14.3 Transport hazard class(es)**  
ADR, ADN, IMDG, IATA  
Class                                      Void

**14.4 Packing group**  
ADR, IMDG, IATA                      Void

**14.5 Environmental hazards:**  
**Marine pollutant:**                      No

**14.6 Special precautions for user** Not applicable.

**UN "Model Regulation":**              Void

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
The following substance(s) in this product is (are) identified by CAS number either in countries not subject to the REACH regulation or in regulations not yet updated with the new naming convention for hydrocarbon solvents.

Hydrocarbons, C14-C19, isoalkanes, cyclics, < 2% aromatics: CAS 64742-46-7

**National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.10.2016

Version: 1

Revision: 01.06.2016

**Trade name: SONAX PROFILINE EX 04/06**

(Contd. of page 6)

IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
IOELV = indicative occupational exposure limit values  
Flam. Liq. 3: Flammable liquids – Category 3  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1

GB