

Printing date 31.05.2017 Version number 2 Revision: 09.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Elvado LSP 5W-30

· Article number: 01.40.85

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

Product category
 PC24 Lubricants, greases, release products

• Process category PROC1 Chemical production or refinery in closed process without likelihood of

exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment

conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-

dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at

dedicated facilities

PROC20 Use of functional fluids in small devices

· Environmental release

category ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)

· Application of the substance /

the mixture Engine oil

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Kroon Oil BV

Dollegoorweg 15 NL-7602 EC ALMELO Tel.: +0031-(0)546-818165

· Further information obtainable

from: Product safety department - vib@kroon-oil.nl

· 1.4 Emergency telephone

number: +31 (0)546 818165 (9 AM to 4 PM, Monday to Friday)

NL - National Poison Information Centre (NVIC):

Tel.nr.: +31 30 - 2748888 - Only for the purpose of informing medical personnel in

case of acute intoxications.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to

Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 Void

· Hazard pictograms Void

· Signal word Void

· Hazard statements Void

· Additional information: EUH210 Safety data sheet available on request.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:		
CAS: 64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	50 -100%
EINECS: 265-157-1	♦ Asp. Tox. 1, H304	
Reg.nr.: 01-2119484627-25		

(Contd. on page 2)

Printing date 31.05.2017 Version number 2 Revision: 09.02.2017

Trade name: Elvado LSP 5W-30

	(Con	td. of page 1)
CAS: 36878-20-3	bis(nonylphenyl)amine	1 - <2.5%
EINECS: 253-249-4	Aquatic Chronic 4. H413	
Reg.nr.: 01-2119488911-28		
CAS: 122-39-4	diphenylamine	0.1 - <1%
EINECS: 204-539-4	 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ♦ STOT RE 2, H373; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

After inhalation:
 After skin contact:
 Supply fresh air; consult doctor in case of complaints.
 Generally the product does not irritate the skin.

After eye contact:
 After swallowing:
 Rinse opened eye for several minutes under running water.
 Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and

delayed No further relevant information available.

 4.3 Indication of any immediate medical attention and special

treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, dry chemical, or foam. Water can be used to cool and protect exposed

material.

· For safety reasons unsuitable

extinguishing agents: Water with full jet

· 5.2 Special hazards arising

from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Wear protective clothing.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust).

Remove from the water surface (e.g. skim or suck off).

• 6.4 Reference to other sections No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Avoid the formation of oil haze.

· Information about fire - and

explosion protection: No special measures required.
7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

· Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about

design of technical facilities: No further data; see item 7.

Revision: 09.02.2017 Printing date 31.05.2017 Version number 2

Trade name: Elvado LSP 5W-30

(Contd. of page 2)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the

workplace:

Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

122-39-4 diphenylamine

WEL | Short-term value: 20 mg/m³ Long-term value: 10 mg/m³

DNEL (Derived No Effect Level) for workers:

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Inhalative Long-term - local effects, worker 5.4 mg/m³ (worker)

Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and

hygienic measures: Wash hands before breaks and at the end of work.

· Respiratory protection: Not required.

· Protection of hands:



Wear gloves for the protection against chemicals according to EN 374.

Oil resistant gloves

· Material of gloves Nitrile rubber, NBR

> **PVC** gloves Neoprene gloves

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed. Goggles recommended during refilling

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· Eye protection:

Form: Liquid Colour: Brown · Odour: Characteristic

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

· Drip point:

Pour point -42 °C (ASTM D97)

· Flash point: >110 °C · Flammability (solid, gas): Not applicable.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

Printing date 31.05.2017 Version number 2 Revision: 09.02.2017

Trade name: Elvado LSP 5W-30

(Contd. of page 3)

	(Conta. or page 3)	
· Explosion limits:		
Lower:	0.6 Vol %	
Upper:	7.0 Vol %	
· Density:	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	: Not determined.	
· Viscosity:		
40 °C	51 mm ² /s (ASTM D445)	
· Solvent content:		
Organic solvents:	0.0 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions
10.4 Conditions to avoid
10.5 Incompatible materials:

Reacts with strong oxidising agents.
No further relevant information available.
No further relevant information available.

· 10.6 Hazardous decomposition

products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic			
Dermal	LD50	>5000 mg/kg (rat)	
		>5000 mg/kg (rabit)	
Inhalative	LC50	>5 mg/l (rat)	

· Primary irritant effect:

• Skin corrosion/irritation
• Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

 CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity

· Reproductive toxicity

· STOT-single exposure

· STOT-repeated exposure · Aspiration hazard

· Carcinogenicity

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. The IP 346 test demonstrates that

all of the oils in this product contain less than 3% extractables. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and

degradability
 Other information:
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.
 No further relevant information available.

· Ecotoxical effects:

• **Remark:**This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the

individual components.

Printing date 31.05.2017 Version number 2 Revision: 09.02.2017

Trade name: Elvado LSP 5W-30

(Contd. of page 4)

· Additional ecological information:

· General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

· European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

CEOTION 14. Transport information		
· 14.1 UN-Number · ADR/ADN, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR/ADN, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR/ADN, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR/ADN, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Annex II of Marpo and the IBC Code	Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances

- ANNEX I None of the ingredients is listed.

· National regulations:

• Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.

Department issuing SDS:
 Contact:
 Product safety department
 Product safety department

(Contd. on page 6)

Printing date 31.05.2017 Version number 2 Revision: 09.02.2017

Trade name: Elvado LSP 5W-30

(Contd. of page 5)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard — Category 4

· Sources