

Printing date 10.02.2017 Version number 3 Revision: 09.02.2017

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Asyntho 5W-30

· Article number: 01.40.60

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

• Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

• Product category PC24 Lubricants, greases, release products

• Process category PROC1 Chemical production or refinery in closed process without likelihood of

exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment

conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-

dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at

dedicated facilities

PROC20 Use of functional fluids in small devices

· Environmental release

category ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)

· Application of the substance /

the mixture Engine oil

· 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Kroon Oil BV

Dollegoorweg 15 NL-7602 EC ALMELO Tel.: +0031-(0)546-818165

· Further information obtainable

from: Product safety department - vib@kroon-oil.nl

· 1.4 Emergency telephone

**number:** +31 (0)546 818165 (9 AM to 4 PM, Monday to Friday)

NL - National Poison Information Centre (NVIC):

Tel.nr.: +31 30 - 2748888 - Only for the purpose of informing medical personnel in

case of acute intoxications.

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

Hazard pictogramsSignal wordVoidVoid

• Hazard statements H412 Harmful to aquatic life with long lasting effects.

• **Precautionary statements** P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)

Printing date 10.02.2017 Version number 3 Revision: 09.02.2017

Trade name: Asyntho 5W-30

(Contd. of page 1)

· Dangerous components:				
CAS: 64742-54-7 EINECS: 265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic  Asp. Tox. 1, H304	50 -100%		
Reg.nr.: 01-2119484627-25				
	Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters,	1 - <2.5%		
EINECS: 283-392-8	zinc salts			
Reg.nr.: 01-2119493626-26	Eye Dam. 1, H318; 🥸 Aquatic Chronic 2, H411; 🗘 Skin Irrit. 2, H315			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

After inhalation:
 After skin contact:
 Supply fresh air; consult doctor in case of complaints.
 Generally the product does not irritate the skin.

After eye contact:
 After swallowing:
 Rinse opened eye for several minutes under running water.
 Do not induce vomiting; call for medical help immediately.

 4.2 Most important symptoms and effects, both acute and

delayed No further relevant information available.

 4.3 Indication of any immediate medical attention and special

treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

#### **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, dry chemical, or foam. Water can be used to cool and protect exposed

material.

· For safety reasons unsuitable

**extinguishing agents:** Water with full jet

· 5.2 Special hazards arising

from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

• **Protective equipment:** Wear self-contained respiratory protective device.

Wear fully protective suit.

### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and

**emergency procedures** Wear protective clothing.

· 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust).

Remove from the water surface (e.g. skim or suck off).

• 6.4 Reference to other sections No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe

**handling** Avoid the formation of oil haze.

· Information about fire - and

explosion protection: No special measures required.

 $\cdot$  7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

**storerooms and receptacles:** Store only in the original receptacle.

· Information about storage in

one common storage facility: Not required.

· Further information about

**storage conditions:** Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

Printing date 10.02.2017 Version number 3 Revision: 09.02.2017

Trade name: Asyntho 5W-30

(Contd. of page 2)

#### **SECTION 8: Exposure controls/personal protection**

· Additional information about

design of technical facilities: No further data; see item 7.

 8.1 Control parameters
 Ingredients with limit values that require monitoring at the

workplace: Contains mineral oil. Under conditions which may generate mists, observe the

OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

### · DNEL (Derived No Effect Level) for workers:

#### 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Inhalative Long-term - local effects, worker 5.4 mg/m³ (worker)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and

hygienic measures: Wash hands before breaks and at the end of work.

· Respiratory protection: Not required.

· Protection of hands:

IIIS J

Wear gloves for the protection against chemicals according to EN 374.

Oil resistant gloves

Material of gloves Nitrile rubber, NBR

PVC gloves Neoprene gloves

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove

material

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed. Goagles recommended during refilling

· Body protection: Protective work clothing

#### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· Eye protection:

Form: Fluid
Colour: Brown
• Odour: Characteristic

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

· Drip point:

Pour point -40 °C (ASTM D97)

Flash point: >110 °C
 Flammability (solid, gas): Not applicable.

• Auto-ignition temperature: Product is not selfigniting.

Printing date 10.02.2017 Version number 3 Revision: 09.02.2017

Trade name: Asyntho 5W-30

(Contd. of page 3)

	(Conta. or page 3)
· Explosive properties: · Explosion limits:	Product does not present an explosion hazard.
Lower:	Not determined.
Upper:	Not determined.
· Density at 20 °C:	0.854 g/cm <sup>3</sup>
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: 40 °C	70.1 mm²/s (ASTM D445)
· Solvent content: Organic solvents:	0.0 %
Solids content:  · 9.2 Other information	0.1 % No further relevant information available.

## **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

conditions to be avoided: To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions
· 10.4 Conditions to avoid

Reacts with strong oxidising agents. No further relevant information available. No further relevant information available.

10.5 Incompatible materials:
10.6 Hazardous decomposition

**products:** No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic			
Dermal	LD50	>5000 mg/kg (rat)	
		>5000 mg/kg (rabit)	
Inhalative	LC50	>5 mg/l (rat)	

· Primary irritant effect:

• Skin corrosion/irritation
• Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for

· Germ cell mutagenicity

· Reproductive toxicity

· Carcinogenicity

reproduction)

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. The IP 346 test demonstrates that

all of the oils in this product contain less than 3% extractables. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and

degradability
 Other information:
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.
 No further relevant information available.

· Ecotoxical effects:

· Remark: Harmful to fish

Printing date 10.02.2017 Version number 3 Revision: 09.02.2017

Trade name: Asyntho 5W-30

(Contd. of page 4)

• Remark: This material is expected to be harmful to aquatic organisms. The product has not

been tested. The statement has been derived from the properties of the individual

components.

· Additional ecological information:

• General notes: Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

• Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

· European waste catalogue

13 02 05\* mineral-based non-chlorinated engine, gear and lubricating oils

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

#### **SECTION 14: Transport information**

· 14.1 UN-Number		
· ADR/ADN, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR/ADN, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR/ADN, ADN, IMDG, IATA		
· Class	Void	
· 14.4 Packing group		
· ADR/ADN, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Annex II of Marpol		
and the IBC Code	Not applicable.	
· UN "Model Regulation":	Void	

#### **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances

ANNEX I None of the ingredients is listed.

· REGULATION (EC) No

**1907/2006 ANNEX XVII** Conditions of restriction: 3

· National regulations:

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Relevant phrases** H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS:
 Contact:
 Product safety department
 Product safety department

Printing date 10.02.2017 Version number 3 Revision: 09.02.2017

Trade name: Asyntho 5W-30

(Contd. of page 5)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· Sources EC/453-2010