

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 3

Revision: 21.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** VatOil SynTech LL-X 5W-40

· **Article number:** VM.20.07

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

· **Product category** PC24 Lubricants, greases, release products

· **Process category** PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC20 Use of functional fluids in small devices

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

· **Environmental release category**

ERC9a Widespread use of functional fluid (indoor)

ERC9b Widespread use of functional fluid (outdoor)

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC7 Use of functional fluid at industrial site

· **Application of the substance / the mixture**

Engine oil

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

VatOil
Dollegoorweg 15
NL-7602 EC ALMELO
Tel.: +31 (0)546 818165

· **Further information obtainable from:**

Product safety department - vib@vatoil.com

· **1.4 Emergency telephone number:**

+31 (0)546 818165 (9 AM to 4 PM, Monday to Friday)

NL - National Poison Information Centre (NVIC):

Tel.nr.: +31 30 - 2748888 - Only for the purpose of informing medical personnel in case of acute intoxications.

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to**

Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 Void

· **Hazard pictograms**

Void

· **Signal word**

Void

· **Hazard statements**

Void

· **Additional information:**

EUH208 Contains Calcium long chain alkarylsulphonate. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 3

Revision: 21.03.2017

Trade name: VatOil SynTech LL-X 5W-40

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-54-7 EINECS: 265-157-1 Reg.nr.: 01-2119484627-25	Distillates (petroleum), hydrotreated heavy paraffinic ☠ Asp. Tox. 1, H304	25- <50%
CAS: 147880-09-9 EC number: 604-611-9	Amines, polyethylenepoly-, reaction products with 1,3-dioxolan-2-one and succinic anhydride monopolyisobutenyl derivs Aquatic Chronic 4, H413	2.5- <10%
CAS: 36878-20-3 EINECS: 253-249-4 Reg.nr.: 01-2119488911-28	bis(nonylphenyl)amine Aquatic Chronic 4, H413	1 - <2.5%
CAS: 68784-26-9 EINECS: 272-234-3 Reg.nr.: 01-2119524004-56	calcium alkylfenatesulphide, long chains Aquatic Chronic 4, H413	1 - <2.5%
CAS: 68784-31-6 EINECS: 272-238-5 Reg.nr.: 01-2119657973-23	phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3- imethylbutyl) esters, zinc salts ☠ Eye Dam. 1, H318; ☠ Aquatic Chronic 2, H411	1 - <2.5%

Additional information: The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General information:** No special measures required.
- After inhalation:** Supply fresh air; consult doctor in case of complaints.
- After skin contact:** Generally the product does not irritate the skin.
- After eye contact:** Rinse opened eye for several minutes under running water.
- After swallowing:** Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, dry chemical, or foam. Water can be used to cool and protect exposed material.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.
Wear fully protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Remove from the water surface (e.g. skim or suck off).

6.4 Reference to other sections

No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 3

Revision: 21.03.2017

Trade name: VatOil SynTech LL-X 5W-40

(Contd. of page 2)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
No special measures required.
Avoid the formation of oil haze.
- **Information about fire - and explosion protection:**
No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)**
No further relevant information available.

SECTION 8: Exposure controls/personal protection


- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

· **DNEL (Derived No Effect Level) for workers:**

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Inhalative	Long-term - local effects, worker	5.4 mg/m ³ (worker)
------------	-----------------------------------	--------------------------------

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not required.
- **Protection of hands:**



Wear gloves for the protection against chemicals according to EN 374.

Oil resistant gloves
- **Material of gloves**
Nitrile rubber, NBR
PVC gloves
Neoprene gloves
Recommended thickness of the material: ≥ 0.35 mm
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Goggles recommended during refilling
- **Body protection:** Protective work clothing

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 3

Revision: 21.03.2017

Trade name: VatOil SynTech LL-X 5W-40

(Contd. of page 3)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	Fluid
Colour:	Brown
Odour:	Characteristic
Change in condition	
Initial boiling point and boiling range: Undetermined.	
Drip point:	
Pour point	-40 °C (ASTM D97)
Flash point:	
>110 °C	
Flammability (solid, gas):	
Not applicable.	
Auto-ignition temperature:	
Product is not selfigniting.	
Explosive properties:	
Product does not present an explosion hazard.	
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Density at 20 °C:	
0.849 g/cm ³	
Evaporation rate	
Not determined.	
Solubility in / Miscibility with water:	
Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	
Not determined.	
Viscosity:	
40 °C	87.4 mm ² /s (ASTM D445)
Solvent content:	
Organic solvents:	0.0 %
9.2 Other information	
No further relevant information available.	

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Dermal	LD50	>5000 mg/kg (rat)
		>5000 mg/kg (rabbit)
Inhalative	LC50	>5 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Sensitisation** For respiratory and skin sensitisation: Not expected to be a sensitiser.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. The IP 346 test demonstrates that all of the oils in this product contain less than 3% extractables.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 3

Revision: 21.03.2017

Trade name: VatOil SynTech LL-X 5W-40

(Contd. of page 4)

- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is not easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.
- **Additional ecological information:**
- **General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|-----------------|
| · 14.1 UN-Number | Void |
| · ADR/ADN, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | Void |
| · ADR/ADN, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | Void |
| · ADR/ADN, ADN, IMDG, IATA | Void |
| · Class | Void |
| · 14.4 Packing group | Void |
| · ADR/ADN, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | No |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances**
- **- ANNEX I** None of the ingredients is listed.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 3

Revision: 21.03.2017

Trade name: VatOil SynTech LL-X 5W-40

(Contd. of page 5)

- **National regulations:**

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H304 May be fatal if swallowed and enters airways.
 H318 Causes serious eye damage.
 H411 Toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

- **Department issuing SDS:**

Product safety department.

- **Contact:**

Product safety department

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

- **Sources**

.