



# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

MSDS Version: E03.00

Date of issue: 06/02/2018

Blend Version: 1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Petrol EGR Extreme Cleaner (Aerosol)  
Product code : W29879

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Maintenance product  
Function or use category : Aerosol propellants

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Wynn's Belgium  
Industriepark-West 46  
9100 Sint-Niklaas - Belgium  
T +32 3 766 60 20 - F +32 3 778 16 56  
[msds@wynns.eu](mailto:msds@wynns.eu) - [www.wynns.com](http://www.wynns.com)

#### 1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45 (NL FR EN DE)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1	H222;H229
Acute Tox. 4 (Dermal)	H312
Acute Tox. 4 (Inhalation:gas)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H335
STOT RE 2	H373

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

Hazardous ingredients : reaction mass of ethylbenzene and xylene

Hazard statements (CLP) : H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H312+H332 - Harmful in contact with skin or if inhaled  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H373 - May cause damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled, oral).

Precautionary statements (CLP) : P261 - Avoid breathing vapours, spray.  
P280 - Wear protective gloves, protective clothing, eye protection.

# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P271 - Use only outdoors or in a well-ventilated area.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0 (REACH-no) 01-2119488216-32	50 - 75	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	10 - 25	Flam. Gas 1, H220
Acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
4-methylpentan-2-ol	(CAS-No.) 108-11-2 (EC-No.) 203-551-7 (EC Index-No.) 603-008-00-8 (REACH-no) 01-2119473979-13	2,5 - 5	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335
Name	Product identifier	Specific concentration limits	
reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0 (REACH-no) 01-2119488216-32	(C >= 10) STOT RE 2, H373	
4-methylpentan-2-ol	(CAS-No.) 108-11-2 (EC-No.) 203-551-7 (EC Index-No.) 603-008-00-8 (REACH-no) 01-2119473979-13	(C >= 25) STOT SE 3, H335	

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. As it is a spray can packaging it is most unlikely that large quantities will be swallowed.

# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. May cause respiratory irritation. Harmful if inhaled. Nausea.
- Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking. Harmful in contact with skin. Tingling/irritation of the skin.
- Symptoms/effects after eye contact : Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. AFFF foam. ABC-powder.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Gas/vapour spreads at floor level: ignition hazard. Gas/vapour flammable with air within explosion limits.
- Explosion hazard : Product is not explosive. Pressurised container: May burst if heated.

### 5.3. Advice for firefighters

- Firefighting instructions : In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable gloves and eye/face protection. protective clothing. Large spills/in enclosed spaces: compressed air apparatus.
- Emergency procedures : Mark the danger area. Stop engines and no smoking. Keep upwind. Prevent flow to low areas. No flames, no sparks. Eliminate all sources of ignition. Wash contaminated clothes.

#### 6.1.2. For emergency responders

- Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent soil and water pollution. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Meet the legal requirements. Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Storage temperature	: ≤ 45 °C
Heat and ignition sources	: Keep away from heat.
Information on mixed storage	: Keep away from strong acids and strong oxidizers.
Storage area	: Meet the legal requirements. Fireproof storeroom. Ventilation along the floor.
Special rules on packaging	: Meet the legal requirements. Labelling according to.
Packaging materials	: Aerosol can.

### 7.3. Specific end use(s)

See product bulletin for detailed information.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Propane (74-98-6)

Belgium	Limit value (ppm)	1000 ppm
---------	-------------------	----------

#### Acetone (67-64-1)

EU	IOELV TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	500 ppm
Belgium	Limit value (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	500 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	1000 ppm
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 8H (ppm)	510 ppm
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (ppm)	1020 ppm
Hungary	AK-érték	1210 mg/m <sup>3</sup>
Hungary	CK-érték	2420 mg/m <sup>3</sup>

#### 4-methylpentan-2-ol (108-11-2)

Belgium	Limit value (mg/m <sup>3</sup> )	106 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	25 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	169 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	40 ppm
Belgium	Remark (BE)	D
France	VME (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
France	VME (ppm)	25 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	85 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	25 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	40 ppm
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	106 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	25 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	170 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	40 ppm

#### reaction mass of ethylbenzene and xylene

##### DNEL/DMEL (Workers)

Acute - systemic effects, inhalation	442 mg/m <sup>3</sup>
Acute - local effects, inhalation	442 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m <sup>3</sup>
Long-term - local effects, inhalation	221 mg/m <sup>3</sup>

##### DNEL/DMEL (General population)

Acute - systemic effects, inhalation	260 mg/m <sup>3</sup>
Acute - local effects, inhalation	260 mg/m <sup>3</sup>

# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### reaction mass of ethylbenzene and xylene

Long-term - systemic effects, oral	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65,3 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65,3 mg/m <sup>3</sup>
PNEC (Water)	
PNEC aqua (freshwater)	0,327 mg/l
PNEC aqua (marine water)	0,327 mg/l
PNEC aqua (intermittent, freshwater)	0,327 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	12,46 mg/kg dwt
PNEC sediment (marine water)	12,46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2,31 mg/kg dwt

### Acetone (67-64-1)

DNEL/DMEL (Workers)	
Acute - local effects, inhalation	2420 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1210 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	62 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	200 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	10,6 mg/l
PNEC aqua (marine water)	1,06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	30,4 mg/kg dwt
PNEC sediment (marine water)	3,04 mg/kg dwt
PNEC (Soil)	
PNEC soil	29,5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

### 4-methylpentan-2-ol (108-11-2)

DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	208 mg/m <sup>3</sup>
Acute - local effects, inhalation	104 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11,8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	83 mg/m <sup>3</sup>
Long-term - local effects, inhalation	83 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	155,2 mg/m <sup>3</sup>
Acute - local effects, inhalation	52,1 mg/m <sup>3</sup>
Long-term - systemic effects, oral	4,2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14,7 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	4,2 mg/kg bodyweight/day
Long-term - local effects, inhalation	14,7 mg/m <sup>3</sup>
PNEC (Water)	
PNEC aqua (freshwater)	0,6 mg/l
PNEC aqua (marine water)	0,06 mg/l
PNEC aqua (intermittent, freshwater)	3,3 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	2,94 mg/kg dwt
PNEC sediment (marine water)	0,3 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,24 mg/kg dwt

# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 4-methylpentan-2-ol (108-11-2)

PNEC (STP)

PNEC sewage treatment plant 1 mg/l

### 8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures. Ensure good ventilation of the work station.

Personal protective equipment

: Protective clothing. Gloves. Protective goggles.



Materials for protective clothing

: Nitrile rubber.

Other information

: Breakthrough time : >30'. Thickness of the glove material >0.15 mm.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: No data available
Odour	: characteristic.
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	:
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 56,5 - 142 °C
Flash point	: -18 °C
Auto-ignition temperature	: 460 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 23,3 hPa @20°C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 854 kg/m <sup>3</sup> @ 20 °C
Solubility	: Partially soluble.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: No data available
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 100 %

Additional information : Physical and chemical properties of the active product without gas. The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.2. Chemical stability

Extremely flammable aerosol. Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from strong acids and strong oxidizers.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. On burning: release of harmful/irritant gases/vapours. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Dermal: Harmful in contact with skin. Inhalation:gas: Harmful if inhaled.

#### Petrol EGR Extreme Cleaner (Aerosol)

ATE CLP (dermal) 1880,342 mg/kg bodyweight

ATE CLP (gases) 7692,308 ppmv/4h

#### reaction mass of ethylbenzene and xylene

LD50 oral rat 3523 mg/kg bodyweight F344/N

LD50 dermal rabbit 12126 mg/kg bodyweight New Zealand White

ATE CLP (oral) 3523 mg/kg bodyweight

ATE CLP (dermal) 1100 mg/kg bodyweight

ATE CLP (gases) 4500 ppmv/4h

ATE CLP (vapours) 11 mg/l/4h

ATE CLP (dust,mist) 1,5 mg/l/4h

#### Acetone (67-64-1)

LD50 oral rat 5800 mg/kg Sprague-Dawley

LD50 dermal rabbit > 15800 mg/kg New Zealand White

LC50 inhalation rat (mg/l) 76 mg/l/4h Carworth Farms-Nelson

ATE CLP (oral) 5800 mg/kg bodyweight

ATE CLP (vapours) 76 mg/l/4h

ATE CLP (dust,mist) 76 mg/l/4h

#### 4-methylpentan-2-ol (108-11-2)

LD50 oral rat 2590 mg/kg bodyweight

LD50 dermal rabbit 2870 mg/kg bodyweight

LC50 inhalation rat (mg/l) > 16 mg/l/4h Wistar

ATE CLP (oral) 2590 mg/kg bodyweight

ATE CLP (dermal) 2870 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled, oral).

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : May have a narcotic effect at high concentrations.

# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : No available data.

##### reaction mass of ethylbenzene and xylene

LC50 fish 1 > 2,6 mg/l @96h

EC50 other aquatic organisms 1 72h 2,2 mg/l

##### Acetone (67-64-1)

LC50 fish 1 96h 5540 mg/l oncorhynchus mykiss

EC50 Daphnia 1 48h 7635 mg/l Daphnia cucullata

NOEC chronic algae 8d 530 mg/l microcystis aeruginosa

##### 4-methylpentan-2-ol (108-11-2)

LC50 fish 1 > 92,4 mg/l @96h Pimephales promelas

EC50 Daphnia 1 48h 337 mg/l Daphnia magna

EC50 other aquatic organisms 1 96h 334 mg/l Pseudokirchneriella subcapitata

NOEC (acute) 48h 288 mg/l Daphnia magna

#### 12.2. Persistence and degradability

##### Acetone (67-64-1)

Persistence and degradability Readily biodegradable.

##### 4-methylpentan-2-ol (108-11-2)

Persistence and degradability Readily biodegradable in water. easily degradable in the soil.

#### 12.3. Bioaccumulative potential

##### Acetone (67-64-1)

Bioaccumulative potential Bioaccumulation unlikely.

#### 12.4. Mobility in soil

##### Acetone (67-64-1)

Ecology - soil Expected to be highly mobile in soil.

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not pierce or burn, even after use. Remove to an authorized waste treatment plant.

European List of Waste (LoW) code : 18 01 06\* - chemicals consisting of or containing dangerous substances  
15 01 11\* - metallic packaging containing a dangerous solid porous matrix (e.g. asbestos), including empty pressure containers

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR) : 1950

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS

Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)

#### 14.3. Transport hazard class(es)

Class (ADR) : 2

Subsidiary risk (IMDG) : 2.1

Subsidiary risk (IATA) : 2.1



# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Danger labels (ADR) : 2.1



### 14.4. Packing group

Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### 14.6.1. Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Transport category (ADR) : 2  
Tunnel restriction code (ADR) : D  
Limited quantities (ADR) : 1I

#### 14.6.2. Transport by sea

EmS-No. (1) : F-D, S-U

#### 14.6.3. Air transport

Instruction "cargo" (ICAO) : 203  
Instruction "passenger" (ICAO) : 203/Y203

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances  
VOC content : 100 %

#### 15.1.2. National regulations

Water hazard class (WGK) : 2 - significant hazard to water

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2

# Petrol EGR Extreme Cleaner (Aerosol)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

---

STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*