

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 21.11.2017

Version: 4

Revision: 19.07.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX TAR REMOVER

Article number: 03045050.04, 03049000-050

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)

Application of the substance / the mixture Car care product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

GHS07

GHS08

Signal word

Danger

Hazard-determining components of labelling:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.11.2017

Version: 4

Revision: 19.07.2017

Trade name: SONAX TAR REMOVER

(Contd. of page 1)

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.
Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Solvent-emulsion mixture**Dangerous components:**

EC No 927-241-2 Reg.nr.: 01-2119471843-32-xxxx	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412	25 - <50%
EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics ⚠ Asp. Tox. 1, H304	25 - <50%
EC No 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	5 - <10%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons	≥30%
aromatic hydrocarbons	≥5 - <15%

Additional information:

Any entry in the EC-column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 15 for additional CAS number information for the substance.

For the wording of the listed hazard phrases refer to section 16.

Hydrocarbon mixture:

Benzene content < 0.1%

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:**

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Drowsiness

Nausea

Reddening, drying and crack formation of the skin

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 21.11.2017

Version: 4

Revision: 19.07.2017

Trade name: SONAX TAR REMOVER

(Contd. of page 2)

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)Nitrogen oxides (NO_x)**5.3 Advice for firefighters****Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

(Contd. on page 4)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.11.2017

Version: 4

Revision: 19.07.2017

Trade name: SONAX TAR REMOVER

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Store in a cool location.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Protect from heat and direct sunlight.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

RCP-TWA (EU)	Long-term value: 1200 mg/m ³ , 165 ppm
	Vapour / Total Hydrocarbons

DNELs

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	DNEL	300 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
Dermal	DNEL	300 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
		300 mg/kg bw/day (worker) (ChronicExposure, SystemicEffects)
Inhalative	DNEL	900 mg/m ³ (consumer) (ChronicExposure, SystemicEffects)
		1500 mg/m ³ (worker) (ChronicExposure, SystemicEffects)

Hydrocarbons, C9, aromatics

Oral	DNEL	11 mg/kg bw/day (consumer) (long term - systemic effects)
Dermal	DNEL	25 mg/kg bw/day (worker) (long term - systemic effects)
Inhalative	DNEL	32 mg/m ³ (consumer) (long term - systemic effects)
		150 mg/m ³ (worker) (long term - systemic effects)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Protection of hands: Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 21.11.2017

Version: 4

Revision: 19.07.2017

Trade name: SONAX TAR REMOVER

(Contd. of page 4)

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)**Eye protection:**

Goggles recommended during refilling

[EN 166]

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Fluid
Colour:	Light brown
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.**Change in condition**

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 110 - 270 °C

Flash point: 37 °C (DIN 51755)**Flammability (solid, gas):** Not applicable.**Decomposition temperature:** Not determined.**Auto-ignition temperature:** Not determined.**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Explosion limits:**

Lower: 0.6 Vol.% (Main ingredient data)
Upper: 7.0 Vol.% (Main ingredient data)

Vapour pressure: Not determined.**Density at 20 °C:** 0,78 - 0,79 g/cm³**Relative density** Not determined.**Vapour density** Not determined.**Evaporation rate** Not determined.**Solubility in / Miscibility with****water:** Not miscible or difficult to mix.**Partition coefficient: n-octanol/water:** Not determined.**Viscosity:****Flow time at 20 °C** 10 - 12 s (DIN EN ISO 2431/4mm)**Kinematic at 40 °C:** < 20,5 mm²/s**9.2 Other information** No further relevant information available.**SECTION 10: Stability and reactivity****10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** Forms explosive gas mixture with air.**10.4 Conditions to avoid**

Keep ignition sources away - Do not smoke.

Protect from heat and direct sunlight.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 21.11.2017

Version: 4

Revision: 19.07.2017

Trade name: SONAX TAR REMOVER

(Contd. of page 5)

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4d	>4951 mg/l (rat) (OECD 403)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5000 mg/m ³ (rat) (OECD 403)

Hydrocarbons, C9, aromatics

Oral	LD50	3592 mg/kg (rat) (OECD 401)
Dermal	LD50	>3160 mg/kg (rabbit) (OECD 402)

Primary irritant effect:**Skin corrosion/irritation**

On the basis of the available data, the classification criteria are not complied with (Conventional Method).
Long-term exposure causes slight irritation of the skin.

Serious eye damage/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).
May cause slight, short-term eye complaints.

Respiratory or skin sensitisation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.**Aspiration hazard**

Viscosity: < 20,5mm²/s (40°C)

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information**12.1 Toxicity**

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxicity:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

LL50 / 96h	>10 - <30 mg/l (Oncorhynchus mykiss)
EL50 / 48h	>22 - <46 mg/l (Daphnia magna)
EL50 / 72h	>1000 mg/l (Pseudokirchneriella subcapitata)
NOELR 72 h	< 1 mg/l (Pseudokirchneriella subcapitata)

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 21.11.2017

Version: 4

Revision: 19.07.2017

Trade name: SONAX TAR REMOVER

(Contd. of page 6)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LLO 96 h	1000 mg/l (Oncorhynchus mykiss)
ELO 48 h	1000 mg/l (Daphnia magna)
ELO 72 h	1000 mg/l (Pseudokirchneriella subcapitata)

Hydrocarbons, C9, aromatics

LL50 / 96h	9.2 mg/l (Oncorhynchus mykiss)
EL50 / 48h	3.2 mg/l (Ceriodaphnia Dubia)
EL50 / 72h	2.6-2.9 mg/l (Pseudokirchneriella subcapitata)

12.2 Persistence and degradability**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Biodegradation	89 % (28d)
----------------	------------

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation	69 % (28d)
----------------	------------

12.3 Bioaccumulative potential No further relevant information available.**12.4 Mobility in soil**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Highly volatile, will partition rapidly to air.

Additional ecological information:**General notes:** The product may not be released into the environment without control.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dangerous waste in accordance with the Directive on the List of Waste Materials

Recommendation Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 13*	solvents
15 01 10*	packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information**14.1 UN-Number**

ADR, IMDG, IATA UN3295

14.2 UN proper shipping nameADR 3295 HYDROCARBONS, LIQUID, N.O.S.
IMDG, IATA HYDROCARBONS, LIQUID, N.O.S.**14.3 Transport hazard class(es)**

ADR, IMDG, IATA

Class 3 Flammable liquids.
Label 3**14.4 Packing group**

ADR, IMDG, IATA III

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 21.11.2017

Version: 4

Revision: 19.07.2017

Trade name: SONAX TAR REMOVER

(Contd. of page 7)

14.5 Environmental hazards:**Marine pollutant:** No**14.6 Special precautions for user** Warning: Flammable liquids.**Transport/Additional information:****ADR****Transport category** 3**Tunnel restriction code** D/E**UN "Model Regulation":** UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

The following substance(s) in this product is (are) identified by CAS number either in countries not subject to the REACH regulation or in regulations not yet updated with the new naming convention for hydrocarbon solvents.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics: CAS 64742-48-9

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics: CAS 64742-47-8

Hydrocarbons, C9, aromatics : CAS 64742-95-6

National regulations:**Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**