

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PROTECTON® POLYESTER RESIN 250 GR
- **Article number:** SER9729
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**
PC9a Coatings and paints, thinners, paint removers
PC9b Fillers, putties, plasters, modelling clay
- **Process category**
PROC10 Roller application or brushing
PROC7 Industrial spraying
PROC10 Roller application or brushing
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Knife filler/ Surfacer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTIP DUPLI B.V.
Wolframweg 2
NL- 8471 XC Wolvega
The Netherlands
Tel: +31 (0)561 694400
Fax: +31 (0)561 694411
e-mail info@nl.motipdupli.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:** +31 (0)561-694400 (09:00h - 17:00h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

Trade name: PROTECTON® POLYESTER RESIN 250 GR

(Contd. of page 1)

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

styrene

methanol

· **Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P281 Use personal protective equipment as required.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P501 Dispose of contents / container in accordance with regional regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

Trade name: PROTECTON® POLYESTER RESIN 250 GR

(Contd. of page 2)

· Dangerous components:		
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32-xxxx	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	25-<50%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X Reg.nr.: 01-2119433307-44	methanol Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370	≤0.5%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures****· General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.**· After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.**· 4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**· 4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media****· Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet**· 5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· 5.3 Advice for firefighters -**· Protective equipment:** Mouth respiratory protective device.**SECTION 6: Accidental release measures****· 6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.**· 6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

Trade name: PROTECTON® POLYESTER RESIN 250 GR

(Contd. of page 3)

- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

100-42-5 styrene

WEL	Short-term value: 1080 mg/m ³ , 250 ppm
	Long-term value: 430 mg/m ³ , 100 ppm

67-56-1 methanol

WEL	Short-term value: 333 mg/m ³ , 250 ppm
	Long-term value: 266 mg/m ³ , 200 ppm
	Sk

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- Avoid contact with the eyes.
- **Respiratory protection:**
- Filter AX
- Filter A/P2
- Not necessary if room is well-ventilated.
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

Trade name: PROTECTON® POLYESTER RESIN 250 GR

(Contd. of page 4)

· **Protection of hands:**

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products
Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Natural rubber, NR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

Natural rubber, NR

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 145 °C (293 °F)

· **Flash point:** 31 °C (87.8 °F)

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 480 °C (896 °F)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

Trade name: PROTECTON® POLYESTER RESIN 250 GR

(Contd. of page 5)

· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
· Vapour pressure at 20 °C (68 °F):	6 hPa (4.5 mm Hg)
· Density at 20 °C (68 °F):	1.12 g/cm ³ (9.35 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	80 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	37.1 %
VOC (EC)	---
	184.2 g/l
· VOC-EU%	16.45 %
· Solids content:	88.6 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

Trade name: PROTECTON® POLYESTER RESIN 250 GR

(Contd. of page 6)

- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
Causes damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Non contaminated packagings may be recycled.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN3269
- **14.2 UN proper shipping name**
- **ADR** 3269 POLYESTER RESIN KIT
- **IMDG, IATA** POLYESTER RESIN KIT

· **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 3 (F+3) Flammable liquids.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

Trade name: **PROTECTON® POLYESTER RESIN 250 GR**

(Contd. of page 7)

· **Label** 3· **IMDG**· **Class** 3.1· **Label** 3· **IATA**· **Class** 3 Flammable liquids.· **Label** 3· **14.4 Packing group**· **ADR, IMDG, IATA** III· **14.5 Environmental hazards:** Not applicable.· **14.6 Special precautions for user** Warning: Flammable liquids.· **Stowage Category** A· **14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code** Not applicable.· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: See· **Transport category** 3· **Tunnel restriction code** E· **IMDG**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: See SP340· **UN "Model Regulation":** UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Directive 2012/18/EU**· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t· **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction:** 3, 40· **National regulations:**· **Other regulations, limitations and prohibitive regulations**· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.03.2018

Version number 4

Revision: 19.03.2018

Trade name: PROTECTON® POLYESTER RESIN 250 GR

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H301 *Toxic if swallowed.*
- H304 *May be fatal if swallowed and enters airways.*
- H311 *Toxic in contact with skin.*
- H315 *Causes skin irritation.*
- H319 *Causes serious eye irritation.*
- H331 *Toxic if inhaled.*
- H332 *Harmful if inhaled.*
- H335 *May cause respiratory irritation.*
- H361d *Suspected of damaging the unborn child.*
- H370 *Causes damage to organs.*
- H372 *Causes damage to the hearing organs through prolonged or repeated exposure.*
- H412 *Harmful to aquatic life with long lasting effects.*

· **Department issuing SDS:** R&D legislation and regulatory advisor

· **Contact:** Mr. K. Smedeman

· **Abbreviations and acronyms:**

- RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- IATA-DGR: *Dangerous Goods Regulations by the "International Air Transport Association" (IATA)*
- ICAO: *International Civil Aviation Organisation*
- ADR: *Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: *International Maritime Code for Dangerous Goods*
- IATA: *International Air Transport Association*
- GHS: *Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: *European Inventory of Existing Commercial Chemical Substances*
- ELINCS: *European List of Notified Chemical Substances*
- CAS: *Chemical Abstracts Service (division of the American Chemical Society)*
- VOC: *Volatile Organic Compounds (USA, EU)*
- PBT: *Persistent, Bioaccumulative and Toxic*
- SVHC: *Substances of Very High Concern*
- vPvB: *very Persistent and very Bioaccumulative*
- Flam. Liq. 2: *Flammable liquids – Category 2*
- Flam. Liq. 3: *Flammable liquids – Category 3*
- Acute Tox. 3: *Acute toxicity – Category 3*
- Acute Tox. 4: *Acute toxicity – Category 4*
- Skin Irrit. 2: *Skin corrosion/irritation – Category 2*
- Eye Irrit. 2: *Serious eye damage/eye irritation – Category 2*
- Repr. 2: *Reproductive toxicity – Category 2*
- STOT SE 1: *Specific target organ toxicity (single exposure) – Category 1*
- STOT SE 3: *Specific target organ toxicity (single exposure) – Category 3*
- STOT RE 1: *Specific target organ toxicity (repeated exposure) – Category 1*
- Asp. Tox. 1: *Aspiration hazard – Category 1*
- Aquatic Chronic 3: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· *** Data compared to the previous version altered.**