

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.07.2016

Version number 34

Revision: 22.07.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: PROTECTON® UNDERBODY WAX COATING 500 ML**
- **Article number: SER9739**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
  - SU21 Consumer uses: Private households / general public / consumers
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category PC9a** Coatings and paints, thinners, paint removers
- **Process category**
  - PROC7 Industrial spraying
  - PROC11 Non industrial spraying
- **Environmental release category**
  - ERC8a Wide dispersive indoor use of processing aids in open systems
  - ERC8d Wide dispersive outdoor use of processing aids in open systems
- **Application of the substance / the mixture** Preparation
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
  - MOTIP DUPLI B.V.
  - Wolfraamweg 2
  - NL- 8471 XC Wolvega
  - The Netherlands
  - Tel: +31 (0)561 694400
  - Fax: +31 (0)561 694411
  - e-mail info@nl.motipdupli.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:** +31 (0)561-694400 (09:00h - 17:00h)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2                      H315                      Causes skin irritation.  
 STOT SE 3                      H336                      May cause drowsiness or dizziness.  
 Aquatic Chronic 3                      H412                      Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.07.2016

Version number 34

Revision: 22.07.2016

Trade name: **PROTECTON® UNDERBODY WAX COATING 500 ML**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Danger· **Hazard-determining components of labelling:**

Naphtha (petroleum), hydrotreated light  
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.\* **SECTION 3: Composition/information on ingredients**· **3.2 Chemical characterisation: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 64742-49-0 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	20-25%
CAS: 64742-48-9 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	12.5-20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220 Press. Gas C, H280	12.5-20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220 Press. Gas C, H280	10-12.5%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31


Printing date 22.07.2016

Version number 34

Revision: 22.07.2016

**Trade name: PROTECTON® UNDERBODY WAX COATING 500 ML**

CAS: 75-28-5  
EINECS: 200-857-2  
Index number: 601-004-00-0  
Reg.nr.: 01-2119485395-27-xxxx

isobutane  
 Flam. Gas 1, H220  
Press. Gas C, H280

(Contd. of page 2)

10-12.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

#### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

**Trade name: PROTECTON® UNDERBODY WAX COATING 500 ML**

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

### 106-97-8 butane

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Not required.

GB

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.07.2016

Version number 34

Revision: 22.07.2016

Trade name: **PROTECTON® UNDERBODY WAX COATING 500 ML**

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

· Form:	Aerosol
· Colour:	According to product specification
· Odour:	Solvent-like
· Odour threshold:	Not determined.

· pH-value: Not determined.

##### · Change in condition

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Not applicable, as aerosol.

· Flash point: <0 °C (<32 °F)  
Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: > 200 °C (> 392 °F)

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### · Explosion limits:

· Lower:	0.6 Vol %
· Upper:	10.9 Vol %

· Vapour pressure at 20 °C (68 °F): 3500 hPa (2625 mm Hg)

· Density at 20 °C (68 °F): 0.66942 g/cm<sup>3</sup> (5.586 lbs/gal)

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

##### · Viscosity:

· Dynamic:	Not determined.
· Kinematic:	Not determined.

##### · Solvent content:

· Organic solvents:	81.2 %
· EU-VOC:	543.4 g/l
· EU-VOC in %:	81.17 %

· Solids content: 18.8 %

· 9.2 Other information: No further relevant information available.

### SECTION 10: Stability and reactivity

· 10.1 Reactivity: No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions: No dangerous reactions known.

· 10.4 Conditions to avoid: No further relevant information available.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.07.2016

Version number 34

Revision: 22.07.2016

Trade name: **PROTECTON® UNDERBODY WAX COATING 500 ML**

(Contd. of page 5)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rabbit)
Inhalative	LC50 / 4h	> 2 mg/l (rat)

**64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	LD50	>15000 mg/kg (rat)
Dermal	LD50	>3160 mg/kg (rab)
Inhalative	LC50 / 4 h	4951 mg/m <sup>3</sup> (rat)

**106-97-8 butane**

Inhalative	LC50 / 4 h	658000 mg/m <sup>3</sup> (rat)
------------	------------	--------------------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

EC50 / 48 h	3 mg/l (Daphnia magna)
EC50 / 72 h	30-100 mg/l (Pseudokirchneriella Subcapitata)
LC50 / 96 h	11.4 mg/l (fish)

**64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

EC50 / 72 h	>1000 mg/l (algae)
LC50 / 48 h	>1000 mg/l (daphnia magna)
LC50 / 96 h	>1000 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.07.2016

Version number 34

Revision: 22.07.2016

**Trade name: PROTECTON® UNDERBODY WAX COATING 500 ML**

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Non contaminated packagings may be recycled.

**SECTION 14: Transport information**

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



- **Class** 2 5F Gases.
- **Label** 2.1

· **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

· **14.4 Packing group**

- **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

- **Marine pollutant:** No

- **14.6 Special precautions for user** Warning: Gases.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.07.2016

Version number 34

Revision: 22.07.2016

**Trade name: PROTECTON® UNDERBODY WAX COATING 500 ML**

(Contd. of page 7)

· <b>Danger code (Kemler):</b>	-
· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** R&D legislation and regulatory advisor

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.07.2016

Version number 34

Revision: 22.07.2016

**Trade name: PROTECTON® UNDERBODY WAX COATING 500 ML**

(Contd. of page 8)

· **Contact:** Mr. K. Smedeman

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*DNEL: Derived No-Effect Level (REACH)*

*PNEC: Predicted No-Effect Concentration (REACH)*

*SVHC: Substances of Very High Concern*

*Flam. Gas 1: Flammable gases – Category 1*

*Aerosol 1: Aerosols – Category 1*

*Press. Gas C: Gases under pressure – Compressed gas*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· **\* Data compared to the previous version altered.**