



Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 3-7-2018 Revision date: 25-2-2021 Supersedes version of: 4-1-2021 Version: 3.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Kroon-Oil SP Fluid 3013
UFI : W7E0-H0QQ-F003-JE1W
Product code : 06.30.21
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Hydraulic oil

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV
Dollegoorweg 15
7602 EC Almelo - Netherlands
T 0031 (0)546 81 81 65
vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhalation:dust,mist) Category 4 H332
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful if inhaled. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

Signal word (CLP) :

Danger

Contains :

Dec-1-ene, dimers, hydrogenated; Distillates (petroleum), hydrotreated heavy paraffinic

Hazard statements (CLP) :

H304 - May be fatal if swallowed and enters airways.

H332 - Harmful if inhaled.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P271 - Use only outdoors or in a well-ventilated area.

P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

P312 - Call a doctor if you feel unwell.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements :

EUH208 - Contains Dibutyl [[bis[(2-ethylhexyl)oxy]phosphinothioyl]thio]succinate, Dibutyl [[(dipropoxyphosphinothioyl)thio]succinate, Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate. May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments :

Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dec-1-ene, dimers, hydrogenated	(CAS-No.) 68649-11-6 (EC-No.) 500-228-5 (REACH-no) 01-2119493069-28	50 – 80	Acute Tox. 4 (Inhalation:dust,mist), H332 Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic (Note L)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	25 – 50	Asp. Tox. 1, H304
Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate	(EC-No.) 948-071-5 (REACH-no) 01-2120785714-43	0,1 – 1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 1, H410
Dibutyl [[bis[(2-ethylhexyl)oxy]phosphinothioyl]thio]succinate	(CAS-No.) 68413-48-9 (EC-No.) 270-220-1 (REACH-no) 01-2120786863-37	< 1	Skin Sens. 1B, H317 Aquatic Chronic 4, H413

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Dibutyl [(dipropoxyphosphinothioyl)thio]succinate	(CAS-No.) 68413-47-8 (EC-No.) 270-219-6 (REACH-no) 01-2120772316-52	< 1	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Methyl methacrylate substance with national workplace exposure limit(s) (GB, IE); substance with a Community workplace exposure limit	(CAS-No.) 80-62-6 (EC-No.) 201-297-1 (EC Index-No.) 607-035-00-6 (REACH-no) 01-2119452498-28	< 0,1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT SE 3, H335
2,6-di-tert-butyl-p-cresol substance with national workplace exposure limit(s) (GB)	(CAS-No.) 128-37-0 (EC-No.) 204-881-4	< 0,1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Ethyl acrylate substance with national workplace exposure limit(s) (GB, IE); substance with a Community workplace exposure limit	(CAS-No.) 140-88-5 (EC-No.) 205-438-8 (EC Index-No.) 607-032-00-X (REACH-no) 01-2119459301-46	< 0,1	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
naphthalene substance with national workplace exposure limit(s) (GB, IE); substance with a Community workplace exposure limit	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2 (REACH-no) 01-2119561346-37	< 0,1	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Comments : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.
Storage temperature : < 40 °C

7.3. Specific end use(s)

No additional information available

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Kroon-Oil SP Fluid 3013	
EU - Indicative Occupational Exposure Limit (IOEL)	
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m ³ - ACGIH TLV (inhalable fraction).

2,6-di-tert-butyl-p-cresol (128-37-0)	
United Kingdom - Occupational Exposure Limits	
Local name	2,6-Di-tert-butyl-p-cresol
WEL TWA (OEL TWA) [1]	10 mg/m ³
WEL STEL (OEL STEL)	30 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Ethyl acrylate (140-88-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylacrylate
IOEL TWA	21 mg/m ³
IOEL STEL	42 mg/m ³
IOEL STEL [ppm]	10 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
Ireland - Occupational Exposure Limits	
Local name	Ethyl acrylate
OEL TWA [1]	20 mg/m ³
OEL TWA [2]	5 ppm
OEL STEL	41 mg/m ³
OEL STEL [ppm]	10 ppm
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values), Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom - Occupational Exposure Limits	
Local name	Ethyl acrylate
WEL TWA (OEL TWA) [1]	21 mg/m ³
WEL TWA (OEL TWA) [2]	5 ppm

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acrylate (140-88-5)	
WEL STEL (OEL STEL)	42 mg/m ³
WEL STEL (OEL STEL) [ppm]	10 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Methyl methacrylate (80-62-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methyl methacrylate
IOEL STEL [ppm]	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
Ireland - Occupational Exposure Limits	
Local name	Methyl methacrylate
OEL TWA [2]	50 ppm
OEL STEL [ppm]	100 ppm
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values), Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom - Occupational Exposure Limits	
Local name	Methyl methacrylate
WEL TWA (OEL TWA) [1]	208 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

naphthalene (91-20-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Naphthalene
IOEL TWA	50 mg/m ³
Notes	(Year of adoption 2010)
Regulatory reference	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations
Ireland - Occupational Exposure Limits	
Local name	Naphthalene
OEL TWA [1]	50 mg/m ³
OEL TWA [2]	10 ppm
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

naphthalene (91-20-3)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	50 mg/m ³
-----------------------	----------------------

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Green.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -63 °C - ASTM D5950 (pour point)
Boiling point	: No data available
Flash point	: 174 °C - ASTM D92 (COC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,817 kg/l (15 °C) - ASTM D4052
Solubility	: Water: Practically not miscible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 17,9 mm ² /s (40 °C) - ASTM D7279
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

Kroon-Oil SP Fluid 3013	
ATE CLP (dust,mist)	1,958 mg/l/4h

Dibutyl [[bis[(2-ethylhexyl)oxy]phosphinothioyl]thio]succinate (68413-48-9)	
LD50 oral	11300 mg/kg bodyweight

2,6-di-tert-butyl-p-cresol (128-37-0)	
LD50 oral	890 mg/kg (rat)

Ethyl acrylate (140-88-5)	
LD50 oral	1120 mg/kg bodyweight
LD50 dermal	3049 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	5900 mg/l

Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate	
LD50 oral rat	300 mg/kg bodyweight

Dec-1-ene, dimers, hydrogenated (68649-11-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1,17 mg/l/4h

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l/4h

naphthalene (91-20-3)	
LD50 oral rat	> 533 mg/kg
LD50 dermal rat	> 2000 mg/kg

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acrylate (140-88-5)	
STOT-single exposure	May cause respiratory irritation.

Methyl methacrylate (80-62-6)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Dibutyl [[bis[(2-ethylhexyl)oxy]phosphinothioyl]thio]succinate (68413-48-9)	
NOAEL (subchronic, oral, animal/male, 90 days)	1000 mg/kg bodyweight

Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight/day

Aspiration hazard : May be fatal if swallowed and enters airways.

Kroon-Oil SP Fluid 3013	
Viscosity, kinematic	17,9 mm ² /s (40 °C) - ASTM D7279

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Ethyl acrylate (140-88-5)	
LC50 - Fish [1]	4,6 mg/l (Oncorhynchus mykiss, 96h)
LC50 - Fish [2]	2,31 – 2,7 mg/l (Pimephales promelas, 96h)
EC50 - Crustacea [1]	7,9 mg/l (Daphnia magna, 48h)
EC50 - Other aquatic organisms [1]	4,4 mg/l waterflea
EC50 - Other aquatic organisms [2]	48 mg/l
ErC50 algae	48 mg/l (Desmodesmus subspicatus, 72h)

Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate	
LC50 - Fish [1]	18 mg/l
EC50 - Crustacea [1]	6,8 mg/l

Dec-1-ene, dimers, hydrogenated (68649-11-6)	
LC50 - Fish [1]	> 1000 mg/l

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 100 mg/l (Pimephales promelas, 96h) (OECD 203 method)

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 - Crustacea [1]	> 10000 mg/l (Gammarus pulex, 48h) (OECD 202 method)
EC50 - Crustacea [2]	> 10000 mg/l (Daphnia magna, 48h) (OECD 202 method)
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)
NOEC chronic fish	≥ 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox, 14/28d)
NOEC chronic crustacea	10 mg/l (Daphnia magna, 21d) (OECD 211 method)

naphthalene (91-20-3)

LC50 - Fish [1]	0,51 mg/l 96h
EC50 - Crustacea [1]	3,4 mg/l Daphnia magna - 48h

12.2. Persistence and degradability

2,6-di-tert-butyl-p-cresol (128-37-0)

Biodegradation	4,5 % (28d) [MIT11]
----------------	---------------------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Biodegradation	31 % (28d) (OECD 301F method)
----------------	-------------------------------

12.3. Bioaccumulative potential

Dibutyl [[bis[(2-ethylhexyl)oxy]phosphinothioyl]thio]succinate (68413-48-9)

Partition coefficient n-octanol/water (Log Pow)	6,5
---	-----

2,6-di-tert-butyl-p-cresol (128-37-0)

BCF - Fish [1]	230 – 2500 mg/l (Cyprinus carpio, 56d, 25°C, [0.05 mg/l])
Partition coefficient n-octanol/water (Log Kow)	5 octanol/water (0.1d)

Ethyl acrylate (140-88-5)

Partition coefficient n-octanol/water (Log Pow)	1,18
---	------

Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate

Partition coefficient n-octanol/water (Log Pow)	4,92 @25°C - pH: 7
Partition coefficient n-octanol/water (Log Kow)	4,5 – 4,6

naphthalene (91-20-3)

Partition coefficient n-octanol/water (Log Pow)	3,01
---	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
Reference code	Applicable on
3(a)	Methyl methacrylate ; Ethyl acrylate
3(b)	Kroon-Oil SP Fluid 3013 ; Dec-1-ene, dimers, hydrogenated ; Distillates (petroleum), hydrotreated heavy paraffinic ; Methyl methacrylate ; Dibutyl [[bis[(2-ethylhexyl)oxy]phosphinothioyl]thio]succinate ; Dibutyl [(dipropoxyphosphinothioyl)thio]succinate ; Ethyl acrylate ; Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3(c)	Kroon-Oil SP Fluid 3013 ; Dibutyl [[bis[(2-ethylhexyl)oxy]phosphinothioyl]thio]succinate ; Dibutyl [[(dipropoxyphosphinothioyl)thio]succinate ; 2,6-di-tert-butyl-p-cresol ; Ethyl acrylate ; Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate
40.	Methyl methacrylate ; Ethyl acrylate

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Child-resistant fastening : Applicable

Tactile warning : Applicable

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
4.2	Symptoms/effects after ingestion	Modified	
16	Abbreviations and acronyms	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.

Kroon-Oil SP Fluid 3013

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains Dibutyl [[bis[(2-ethylhexyl)oxy]phosphinothioyl]thio]succinate, Dibutyl [[(dipropoxyphosphinothioyl)thio]succinate, Reaction mass of C12-14 tert-alkylamines and dimethyl hydrogen phosphate and methyl dihydrogen phosphate. May produce an allergic reaction.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.